

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Туре

## **BR2110 Type BR BRKR 110A/2 Pole 120/240V 10K** *Eaton Corp*

Catalog Number	BR2110
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, 110 A, 10 Kaic, Two-Pole, 120/240V, BR, Common Breaker Trip, #4-1/0 Awg Cu/AI, Q28, BR, Type BR Loadcenters
Weight per unit	0.8000 (lbs/each)
Product Category	2 Pole Standard Trip Plug-In
eatures	
dimensions	3.0000 IN X 2.0000 IN X 3.0000 IN
interrupt rating	10 kAIC
Poles	2
Trip Type	Common breaker trip
Voltage Rating	120/240 V
escriptions	
Description	TYPE BR BRKR 110A/2 POLE 120/240V 10K
extra long description	ETN BR2110 Type BR Breaker 110A/2 P
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR Thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, 110 A, 10 kAIC, Two-pole, 120/240V, BR, Common breaker trip, #4-1/0 AWG Cu/AI, Q28, BR, Type BR Loadcenters
Product Type	Type BR Breaker 110A/2 Pole 120/240V 10K
lanufacturer Information	
Brand	Eaton
GTIN	00786676384278
Manufacturers Part Number	BR2110
UPC	786676384278

Category Description Loadcenter Plug In Breakers and Accessories

Thermal magnetic circuit breakers



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	0.8
<b>Uses, Certifications, and Standards</b>	
Application	Datacenters - IT Space: CI and Hyper ConvergedMarine Vessels and Equipment - Marine Vessels and Equipment - OtherOtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional Energy
standard	UL 489, Federal Specifications Classification W-C375