

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BRN235GF BR 2 Pole 35A GFST, 120/2 Eaton Corp

Catalog Number	BRN235GF
Manufacturer	Eaton Corp
Description	Eaton BR Gfci Circuit Breaker, Ground Fault Personnel Protection Circuit Breakers, Pigtail Neutral, 35 A, 10 Kaic, Two-Pole, 120/240 V, GFTCB, Common, #14-4 Awg, Ground Fault Circuit Interrupter, GFI
Weight per unit	1.0 (lbs/each)
Product Category	Distribution Equipment
Features	
dimensions	4.2500 IN X 3.0000 IN X 2.0000 IN
Descriptions	
Description	BR 2 POLE 35A GFST, 120/2
extra long description	ETN BRN235GF BR 2 POLE 35A GFST, 12
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR
	loadcenters, spa panels, meter breakers and sub panels. They are
	designed for a wide range of applications such as high
	short-circuit interrupt, series rating combinations with upstream
	main breakers, thermal magnetic, AFCI, GFCI, equipment
	protection and dual function AF/GF.
Long Description	EATON BR GFCI CIRCUIT BREAKER, GROUND FAULT PERSONNEL
	PROTECTION CIRCUIT BREAKERS, PIGTAIL NEUTRAL, 35 A, 10
	KAIC, TWO-POLE, 120/240 V, GFTCB, COMMON, #14-4 AWG, GROUND FAULT CIRCUIT INTERRUPTER, GFI
Product Type	BR 2 Pole 35A GFST, 120/240V, 10 Kaic
Manufacturer Information Brand	Eaton
GTIN	00786676043861
Manufacturers Part Number	BRN235GF
UPC	786676043861
Taxonomies, Classifications, and Category Description	Foult Songing Prockars (AFCL/CFCL)
Туре	
Packaging	1
Carton	1
Weight Per each	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application

standard

Generation - Renewable Energy - Alternative EnergyGeneration -Conventional Energy - Conventional EnergyOtherMarine Vessels and Equipment - Marine Vessels and Equipment -OtherDatacenters - IT Space: CI and Hyper Converged UL 489,UL 943