

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **BRNSURGE10 Type BR 2 Pole Surge Arre** *Eaton Corp*

Eaton corp	
Catalog Number	BRNSURGE10
Manufacturer	Eaton Corp
Description	Eaton Type BR Circuit Breaker Surge Protective Device, Two Pole, Pigtailz Neutral Surge Protective Device, 10 Ka
Weight per unit	0.5480 (lbs/each)
Product Category	Distribution Equipment
Features	
dimensions	3.6000 IN X 3.5000 IN X 2.2500 IN
<b>Dimensions and Weight</b>	
Depth	3.6
Height	2.25
Width	3.5
Descriptions	
Description	TYPE BR 2 POLE SURGE ARRE
extra long description	EWD BRNSURGE10 TYPE BR 2 POLE SURGE
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	EATON TYPE BR CIRCUIT BREAKER SURGE PROTECTIVE DEVICE, TWO POLE, PIGTAILZ NEUTRAL SURGE PROTECTIVE DEVICE, 10 KA
Product Type	Type BR 2 Pole Surge Arrester
Manufacturer Information	
Brand	Eaton
GTIN	00786689880828
Manufacturers Part Number	BRNSURGE10
UPC	786689880828

## **Taxonomies, Classifications, and Categories**

Category Description	Loadcenter Plug In Breakers and Accessories
Туре	Plug on module surge protection device



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	0.548
Uses, Certifications, and Sta	ndards
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	OtherOther
standard	UL 1449,cUL Certified