

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### C19 1/2" Alu C MK9 Conduit Body Crouse-Hinds

Catalog Number	C19
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body, Copper-Free Aluminum, C Shape, 1/2"
Weight per unit	0.3100 (lbs/each)
Product Category	Alum

#### **Features**

dimensions 4.9700 IN X 1.3800 IN X 1.4100 IN

#### Material, Color, and Finish

Fire inde	Linetus at a d
Finish	Untreated
	9110 9409

#### **Dimensions and Weight**

Height	1-3/8
Hub Size	1/2 in
Length	5
Width	1-3/8

#### **Descriptions**

Description	1/2" ALU C MK9 CONDUIT BODY
extra long description	CRS-H C19 1/2 NPT CST AL C MARK 9 C
Features	Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, C shape, 1/2"
Product Type	1/2 NPT CST AI C Mark 9 CNDT Body

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274122502
UPC	782274122502

#### **Taxonomies, Classifications, and Categories**

Category Description	Form 9 condulets, covers & gaskets
Туре	Conduit outlet body



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

110	$\Delta \mathbf{I}$	<i>,</i> ~	$\sim$	 •
Pa	( . R			 Ш
·	v	١u	м	 •

Carton	1	
Package	10	
Weight Per each	0.31	

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D