

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



C27SA 3/4" Alu C FM7 Conduit Rody

Catalog Number	C27SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 7 Conduit Outlet Body Copper-Free Aluminum, C Shape, 3/4"
Weight per unit	0.4500 (lbs/each)
Product Category	Alum
Features	
dimensions	6.0000 IN X 1.5600 IN X 1.6300 IN
Form	Form 7
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	1-5/8
Hub Size	3/4 in
Length	6
Width	1-9/16
Descriptions	
Description	3/4" ALU C FM7 CONDUIT BODY
extra long description	CRS-H C27 SA 3/4 NPT AL C FORM 7 CN
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 7 bodies are offered in 11 different shapes to provide the most flexible offering on the market. Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations. Many shapes and sizes are available for rigid threaded conduit. Our Form 7 family features
Long Description	an exclus Eaton Crouse-Hinds series Condulet Form 7 conduit outlet body,
5 1	Copper-free aluminum, C shape, 3/4"
Product Type	3/4 NPT AI C Form 7 CNDT Body
Manufacturer Information	

Mar

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274122618
Manufacturers Part Number	C27 SA
UPC	782274122618



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, C	Classificati	ons, and	Categories
---------------	--------------	----------	------------

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Package	5
Weight Per each	0.45
Uses, Certifications, and Stand	lards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D