


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## **C4LG6 4-In LT Gray CVR P/FT**Panduit Corporation

Catalog Number	C4LG6
Manufacturer	Panduit Corporation
Description	The C4LG6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.37" X 4.25" (9.4 MM X 108 MM) and 6' (1.83 M) Long. Color Light Gray.
Weight per unit	1.1 (lbs/each)
Product Category	Wiring Duct & Accessories
Features	
connection	Snap-on
media	Yes
Material, Color, and Finish	
Color	Gray
<b>Dimensions and Weight</b>	
Length	NA
Width	4.25
Descriptions	
Description	4-IN LT GRAY CVR P/FT
extra long description	PAN C4LG6 Panduct® C4LG6 Flush Duct
Long Description	The C4LG6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.37" x 4.25" (9.4 mm x 108 mm) and 6' (1.83 m) long. Color Light Gray.
Product Type	Panduct® C4LG6 Flush Duct Cover
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983231409
Manufacturers Part Number	C4LG6
UPC	074983231409



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	WIRE DUCT AND COVERS
Туре	Flushed Duct Cover
Availability	
minimum qty	6
Packaging	
Carton	6
Package	120
Weight Per foot	1.06
Uses, Certifications, and Standards	
Application	Cover for Wiring Duct
standard	CE Compliant; CSA Certified; Flammability Ratings: UL94 V-0; RoHS

Compliant; UL Recognized