

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### C67SA 2" Alu C FM7 Conduit Body Crouse-Hinds

Catalog Number	C67SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 7 Conduit Outlet Body, Copper-Free Aluminum, C Shape, 2"
Weight per unit	
Product Category	Alum

#### **Features**

9.1900 IN X 3.0000 IN X 3.1300 IN dimensions Form 7 Form

#### Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

#### **Dimensions and Weight**

Height	3-1/8	
Hub Size	/ 111	
Length	9-3/16	
Width	3	

#### **Descriptions**

Description	2" ALU C FM7 CONDUIT BODY
extra long description	CRS-H C67 SA 2 NPT AL C FORM 7 CNDT
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 7 bodies are offered in 11 different shapes to provide the most flexible offering on the market. Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations. Many shapes and sizes are available for rigid threaded conduit. Our Form 7 family features an exclus
Long Description	Eaton Crouse-Hinds series Condulet Form 7 conduit outlet body, Copper-free aluminum, C shape, 2"
Product Type	2 NPT AI C Form 7 CNDT Body
nufacturer Information	

#### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274746234
Manufacturers Part Number	C67 SA
UPC	782274746234



standard

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS	
Туре	Conduit outlet body	
Packaging		
Carton	1	
Package	2	
	1.85	
Uses, Certifications, and Standards Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other	

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D