



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

C989 3-1/3" Alu C MK9 Conduit Body

Crouse-Hinds



Catalog Number	C989
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body, Copper-Free Aluminum, C Shape, 3-1/2"
Weight per unit	9.2 (lbs/each)
Product Category	Alum

Features

dimensions	18.7500 IN X 6.2500 IN X 5.6900 IN
------------	------------------------------------

Material, Color, and Finish

Finish	Untreated
--------	-----------

Dimensions and Weight

Height	5-11/16
Hub Size	3-1/2 in
Length	18-3/4
Width	6-1/4

Descriptions

Description	3-1/3" ALU C MK9 CONDUIT BODY
extra long description	CRS-H C989 3 1/2 NPT CST AL C MARK
Features	Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, C shape, 3-1/2"
Product Type	3 1/2 NPT CST Al C Mark 9 CNDT Body

Manufacturer Information

Brand	Eaton
GTIN	00782274125701
Manufacturers Part Number	C989
UPC	782274125701

Taxonomies, Classifications, and Categories

Category Description	Form 9 condulets, covers & gaskets
Type	Conduit outlet body



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	9.1999

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D