

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Weight Per each

CCV2225 CCV BRKR 225A/2 Pole 120/240V 10K Eaton Corp

Catalog Number	CCV2225
Manufacturer	Eaton Corp
Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant Main Circuit Breaker, 225 A, 10 Kaic, Two-Pole, 120/240 V, #2/0 Awg-300 Kcmil Cu/Al, CCV, Type Ecc Unit Enclosures
Weight per unit	2.5 (lbs/each)
Product Category	Main Circuit Breaker Modules
atures	
dimensions	8.0000 IN X 4.5000 IN X 5.5000 IN
interrupt rating	10 kAIC
Poles	Two-pole
Voltage Rating	120/240 V
scriptions	
Description	CCV BRKR 225A/2 POLE 120/240V 10K
extra long description	ETN CCV2225 CCV BREAKER 225A/2 POLE
Features	Eaton's main circuit breakers are used in a variety of applications including the main or emergency disconnect on the outside of a house, a tenant main breaker in group metering stacks and feed-through lug blocks specifically designed for sub-feeding from an existing panel. Main breakers are available with a variety of accessories including shunt trip, bell alarms and auxiliary switches.
Long Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant main circuit breaker, 225 A, 10 kAIC, Two-pole, 120/240 V, #2/0 AWG-300 kcmil Cu/AI, CCV, Type ECC unit enclosures
Product Type	CCV Breaker 225A/2 Pole 120/240V 10K
anufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00786685368641
Manufacturers Part Number	CCV2225
UPC	786685368641
xonomies, Classifications, and C	ategories
Category Description	
Туре	-
ckaging	
Carton	1

2.5

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

oo, con timoationo, ana otanaai ao	
Application	OtherDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherGeneration - Renewable Energy - Alternative
	EnergyGeneration - Conventional Energy - Conventional Energy
standard	UL 489