

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Package

Weight Per each

CFX5WHX Raceway Coupling Panduit Corporation

Catalog Number	CFX5WHX
Manufacturer	Panduit Corporation
Description	The Coupler Fitting Is Used to Efficiently Manage Cable Placement. It Is Designed to Be Used With LD5, and LDPH5 Surface Raceway and Is A 1 Inch Length. It Meets Tia/Eia Standards, Is UL5A Listed, and Is UI Compliant. It Features A Snap-On Installation, Is Made Of Abs Plastic and Is White.
Weight per unit	1.0 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray
Features	
Cover Type	Coupler
Material	ABS
media	Yes
Dimensions and Weight	
Length	1
Width	1.11
Descriptions	
Description	RACEWAY COUPLING
extra long description	PAN CFX5WH-X SURFACE RACEWAY, LD5 /
Long Description	The coupler fitting is used to efficiently manage cable placement It is designed to be used with LD5, and LDPH5 surface raceway and is a 1 inch length. It meets TIA/EIA Standards, is UL5A Listed, and is UL Compliant. It features a snap-on installation, is made of ABS plastic and is white.
Product Type	Surface Raceway, LD5 / LDPH5 Coupler, Power Rated, White
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983529452
Manufacturers Part Number	CFX5WH-X
UPC	074983529452
Taxonomies, Classifications, and G	Categories
Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Туре	Power Rated Fitting
Packaging Carton	10

50

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

es, cei illications, anu stanua	ius
Application	Surface Raceway Products Provide Maximum Flexibility for
	Routing, Protecting, and Concealing High-Performance Copper,
	Voice, Video, Fiber Optic, and Electrical Wiring within any
	Enterprise Environment to Provide an Innovative and Satisfying
	Office Environ
standard	UI94V-0, Ft4, Meets TIA/EIA Standards, UL5A Listed, UL
	Compliant