

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CG2575S 3/4" STL STR Cord Conn *Appleton/Oz Gedney*

Catalog Number	CG2575S
Manufacturer	Appleton/Oz Gedney
Description	Straight Liquidtight Strain Relief Connector, Size: 3/4 In,
	Conductor Range: 1/4 - 3/8 In, Material: Machined Steel, Color:
	Green Label, Nema Rating: Nema 3R, Connection: Threaded Hub
	Dimensions: 1-1/4 In Height, Standard: Class I, Divi
Weight per unit	0.2500 (lbs/each)
Product Category	Cable & Cord Grips
eatures	
connection	Threaded Hub
Material, Color, and Finish	
Color	/:Green
Dimensions and Weight	
Size	3/4
escriptions (
Description	3/4" STL STR CORD CONN
extra long description	APP CG-2575S 3/4 IN STL L-T CRD&CBL
Long Description	Straight Liquidtight Strain Relief Connector, Size: 3/4 IN,
	Conductor Range: 1/4 - 3/8 IN, Material: Machined Steel, Color:
	Green Label, Nema Rating: NEMA 3R, Connection: Threaded Hub
	Dimensions: 1-1/4 IN Height, Standard: Class I, Divi
Product Type	3/4 In STL L-T CRD&CBL Conn
Special Features	Color coded identification label clearly states the catalog numbe
	and minimum-maximum cable diameter range for which the
	connector is designed; For use in wet or dry locations sealing
	electrical connections against dust and dirt, oil, water or other
	atmosphere containing moisture; Machined steel cap; Neoprene
	sealing grommet; Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting internal
	wiring connections against external tension on cable or
	cord;Steel or Tefl
Manufacturer Information	
Brand	Appleton
GTIN	00781381449298
Manufacturers Part Number	CG-2575S
UPC	781381449298



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cat	tegories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Straight Liquidtight Strain Relief Connector
Packaging	
Carton	1
Package	25
Weight Per each	0.25
Uses, Certifications, and Standards	
Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or
	Control Cord And Cable
nema rating	3R
standard	Class I, Division 2, Class II, Division 1 And 2 Class III, UL 514B,

E14817, CSA C22.2 No. 18.3, 065178