



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CG610 CG Mle STR 3/4 .560-.625 *Pass & Seymour/Legrand*

Catalog Number	CG610
Manufacturer	Pass & Seymour/Legrand
Description	Cord Grip Male Straight, 3/4-Inch NPT, 0.500-Inch-0.625-Inch
Weight per unit	2.1 (lbs/each)
Product Category	Cable & Cord Grips

Features

Cable Size	NPT Size: 3/4; Cable Dia. Range: 0.560-0.625
Cable Type	Various Types of Electrical Conductor/Cable
load	Strain Relief Grips are designed to prevent tension from being transferred to junctions and terminals on electrical cord, cable and conduit, therefore providing a more secure electrical structure.

Descriptions

Construction	Various Types of Pulling, Support and Strain Relief Grips
Description	CG MLE STR 3/4 .560-.625
extra long description	P&S CG610 CG MLE STR 3/4 .560-.625
Long Description	Cord Grip Male Straight, 3/4-inch NPT, 0.500-inch-0.625-inch
Product Type	CG Mle STR 3/4 .560-.625
Special Features	Deluxe cord grips are woven of stainless steel mesh with an aluminum body for corrosion resistance. They are offered in single/double weave construction to help absorb direct pull, to resist flexing and binding, and to eliminate strain. They are recommended for indoor or outdoor use where subjected to moisture in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. Deluxe grips are suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and C

Manufacturer Information

Brand	Pass and Seymour
GTIN	00785007996517
Manufacturers Part Number	CG610
UPC	785007996517

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Type	Flexcor® Deluxe Strain Relief Cord Grip - Straight Male

Packaging

Carton	1
Weight Per each	2.08



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Industrial
Capacity	Various Cable Diameter Ranges
Mounting	Consult the Factory for Mounting Recommendations
standard	UL/CSA Approval (consult factory)