


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





CGB197 1/2" Dia Male Cord Grip (.750-.875) *Crouse-Hinds*

Catalog Number	CGB197
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CGB Cable Gland, Cable Range Min/Max: 0.750-0.875", Non-Armoured and Tray Cable, Non-Armoured, Steel, General Purpose, 1/2" NPT
Weight per unit	0.5200 (lbs/each)
Product Category	Cable & Cord Grips
Features	
connection	Male NPT
dimensions	2.3800 IN X 1.6600 IN X 1.6600 IN
Material	Steel Body and Gland Nut, Neoprene Seal
Material, Color, and Finish	
Finish	Zinc Electroplated With Chromate Coated
Dimensions and Weight	
Size	1/2 in
Descriptions	
Description	1/2" DIA MALE CORD GRIP (.750875)
extra long description	CRS-H CGB197 1/2 NPT MALE CORD/CAB
Features	They are also listed for use with tray cable types TC, TC-ER, TC-ER-HLA, ITC, ITC-ER, ITC-HL, PLTC and PLTC-ER. When installed in accordance with NEC501.10(B)(4), CGB, CGD, CGE and CGFP non-armoured glands are suitable for use in Class I, Division 2 hazardous locations. Crouse-Hinds series CGB, CGD, CGE and CGFP non-armoured glands are installed to provide a means for passing a cord, unarmoured cable or flexible conduit into an enclosure. The glands form an environmental seal for cord or unarmoured round
Long Description	Eaton Crouse-Hinds series CGB cable gland, Cable range min/max: 0.750-0.875", Non-armoured and tray cable, Non-armoured, Steel, General purpose, 1/2" NPT
Product Type	1/2 NPT Male Cord/Cab FTG Neo Bush
Special Features	Non-Armored Gland, With Sealing Gasket, Cord Size 0.750 To 0.875 In



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer In	ntormation

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274131603
Manufacturers Part Number	CGB197
UPC	782274131603

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland

Packaging

Magirig		
Carton	1	
Package	10	
Weight Per each		

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 2
standard	UL (CANADA AND US), CUL
Temperature Rating	-25 To 40 Deg C