

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CGB296SA 3/4" Alu Dia Male Cord Grip (.625-.750) Crouse-Hinds

Catalog Number	CGB296SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CGB Cable Gland, Cable Range
	Min/Max: 0.625-0.750", Non-Armoured and Tray Cable,
	Non-Armoured, Aluminum, General Purpose, 3/4" NPT
Weight per unit	0.2200 (lbs/each)
Product Category	Cable & Cord Grips
Features	
connection	Male NPT
dimensions	2.3800 IN X 1.7800 IN X 1.7800 IN
Material	Steel Body, Aluminum Gland Nut, Neoprene Seal
Material, Color, and Finish	
Finish	Zinc Electroplated With Chromate Coated
Dimensions and Weight	
Size	3/4 in
Descriptions	
Description	3/4" ALU DIA MALE CORD GRIP (.625750)
extra long description	CRS-H CGB296 SA 3/4 NPT MALE AL COR
Features	They are also listed for use with tray cable types TC, TC-ER,
	TC-ER-HLA, ITC, ITC-ER, ITC-HL, PLTC and PLTC-ER. When
	installed in accordance with NEC501.10(B)(4), CGB, CGD, CGE and
	CGFP non-armoured glands are suitable for use in Class I, Divisior
	2 hazardous locations. Crouse-Hinds series CGB, CGD, CGE and
	CGFP non-armoured glands are installed to provide a means for
	passing a cord, unarmoured cable or flexible conduit into an
	enclosure. The glands form an environmental seal for cord or
	unarmoured round
Long Description	Eaton Crouse-Hinds series CGB cable gland, Cable range
	min/max: 0.625-0.750", Non-armoured and tray cable,
	Non-armoured, Aluminum, General purpose, 3/4" NPT
Product Type	3/4 NPT Male AI Cord/Cab FTG Neo Bush
Special Features	Non-Armored Gland, Cord Size 0.625 To 0.750 In



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274100777
Manufacturers Part Number	CGB296 SA
UPC	782274100777
Taxonomies, Classifications, and	Categories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland
Packaging	
Carton	1
Package	10
Weight Per each	0.22
Uses, Certifications, and Standar	ds
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 2
standard	UL (CANADA AND US), CUL
Temperature Rating	-25 To 40 Deg C