

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CGB298 3/4" Dia Male Cord Grip (.875-1.0) Crouse-Hinds

Catalog Number	CGB298
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CGB Cable Gland, Cable Range
	Min/Max: 0.875-1.000", Non-Armoured and Tray Cable,
	Non-Armoured, Steel, General Purpose, 3/4" NPT
Weight per unit	1.2 (lbs/each)
Product Category	Cable & Cord Grips
Features	
connection	Male NPT
dimensions	3.1300 IN X 2.2500 IN X 2.2500 IN
Material	Aluminum Body and Gland Nut, Neoprene Seal
Material, Color, and Finish	
Finish	Zinc Electroplated With Chromate Coated
Dimensions and Weight	
Size	3/4 in
	5/ + 11
Descriptions	
Description	3/4" DIA MALE CORD GRIP (.875-1.0)
extra long description	CRS-H CGB298 3/4 NPT MALE CORD/CAB
Features	They are also listed for use with tray cable types TC, TC-ER,
	TC-ER-HLA, ITC, ITC-ER, ITC-HL, PLTC and PLTC-ER. When
	installed in accordance with NEC501.10(B)(4), CGB, CGD, CGE and
	CGFP non-armoured glands are suitable for use in Class I, Division
	2 hazardous locations. Crouse-Hinds series CGB, CGD, CGE and
	CGFP non-armoured glands are installed to provide a means for
	passing a cord, unarmoured cable or flexible conduit into an
	enclosure. The glands form an environmental seal for cord or unarmoured round
Long Description	Eaton Crouse-Hinds series CGB cable gland, Cable range
	min/max: 0.875-1.000", Non-armoured and tray cable,
	Non-armoured, Steel, General purpose, 3/4" NPT
Product Type	2/4 NPT Malo Cord/Cab ETC Noo Bush



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274133201
Manufacturers Part Number	CGB298
UPC	782274133201
Taxonomies, Classifications, and Cate	egories
	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland
Packaging	
Carton	1
Package	5
Weight Per each	1.18
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 2
standard	UL (CANADA AND US), CUL
Temperature Rating	-25 To 40 Deg C