

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## CGB395 1" Dia Male Cord Grip (.500-.625) Crouse-Hinds

Catalog Number	CGB395
Manufacturer	Crouse-Hinds
Description	Cord Gland, Steel With Zinc Electroplate and Chromate Finish Coat (Body, Gland Nut);Neoprene (Bushing) Material, CGB Model, 0.5 to 0.625 In Cable/Cord Size, 2.376 In Length, 1.656 In Diameter, Straight Male Connection, 1 In Thread Size, -25 °C Operating Temperature, +40 °C Operating Temperature, 0.59 LB
Weight per unit	0.5900 (lbs/each)
Product Category	Cable & Cord Grips
eatures	
connection	Male NPT
dimensions	2.3800 IN X 1.6600 IN X 1.6600 IN
Material, Color, and Finish	
Finish	Zinc Electroplated With Chromate Coated
Dimensions and Weight	·
Size	1 in
Descriptions	
Description	1" DIA MALE CORD GRIP (.500625)
extra long description	CRS-H CGB395 1 NPT MALE CORD/CAB FT
Features	They are also listed for use with tray cable types TC, TC-ER, TC-ER-HLA, ITC, ITC-ER, ITC-HL, PLTC and PLTC-ER. When
	installed in accordance with NEC501.10(B)(4), CGB, CGD, CGE and CGFP non-armoured glands are suitable for use in Class I, Divisior 2 hazardous locations. Crouse-Hinds series CGB, CGD, CGE and CGFP non-armoured glands are installed to provide a means for passing a cord, unarmoured cable or flexible conduit into an enclosure. The glands form an environmental seal for cord or unarmoured round
Nanufacturer Information	
Brand	Eaton
GTIN	00782274134000
UPC	782274134000
axonomies, Classifications, and	Categories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packag	ıng
--------	-----

Carton	1	
Package	10	
Weight Per each	0.59	

## Uses, Certifications, and Standards

Enclosure	Class I Div 2	
standard	UL (CANADA AND US), CUL	
Temperature Rating	-25 To 40 Deg C	