


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Product Type

Special Features

CH30B100R 1PH/CH Loadcenter 100A 10KAIC MCB 30 Cir. Cu Bus N

Soon Eaton Corp	
Catalog Number	CH30B100R
Manufacturer	Eaton Corp
Description	Eaton CH Main Breaker Loadcenters, Standard, Main Breaker, 100 A, D, Copper, Nema 3R, Metallic, 10 Kaic, CH, 30, 30, Three-Wire, Single-Phase, #6-1/0 Awg, Overhead, 120/240 V
Weight per unit	34.2 (lbs/each)
Product Category	
Features	
amperage rating	100
dimensions	20 1200 IN V 14 2100 IN V E 1000 IN
interrupt rating	
media	Voc
number of spaces	30
Phase	1
Voltage Rating	120/240 V
Dimensions and Weight	
Depth	29.13
Height	5.19
Size	D
Width	14.31
Descriptions	
Description	1PH/CH LOADCENTER 100A 10KAIC MCB 30 CIR. CU BUS N
extra long description	ETN CH30B100R Eaton CH main breaker
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for
	power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box
	or even a fuse box, the main function is to take electricity
	supplied by the utility and distribute it throughout the home to
	feed lights and receptacles. Covers are typically packaged
	separately and available as surface or flush mount.
Long Description	Eaton CH main breaker loadcenters, Standard, Main breaker, 100
,	A,D,Copper,NEMA 3R,Metallic,10
	kAIC,CH,30,30,Three-wire,Single-phase,#6-1/0

AWG, Overhead, 120/240 V

Standard

Eaton CH Main Breaker Loadcenter



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information		
Brand	Eaton	
GTIN	00782113097824	
Manufacturers Part Number	CH30B100R	
UPC	782113097824	
Taxonomies, Classifications, and C	Categories	
Category Description	LOADCENTERS & COVERS	

Main breaker loadcenter

Availability	

Type

Status Inactive

Packaging

Carton 1
Weight Per each 34.2

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels
	and EOEMs
standard	UL 67,UL 50