

# Eaton CHCC1DIU

Catalog Number: CHCC1DIU

Eaton Bussmann series CHCC modular fuse holder, 48 Vdc, 30A, Single-pole, With indicator



## General specifications

Product Name Catalog Number

Eaton Bussmann series CHCC modular fuse holder CHCC1DIU

UPC

051712362665

Product Length/Depth

0.69 in

Product Height

2.91 in

Product Width

3.28 in

Product Weight

0.22 lb

Warranty

Not Applicable

Compliances

RoHS Compliant

Certifications

Contact Manufacturer

## Electrical rating

### Amperage Rating

30 A

### Voltage rating

48 Vdc

## Physical details

### Number of Poles

Single-pole

### Operating temperature - max

90 °C

### Operating temperature - min

-20 °C

## General information

### Class

Class CC

### Used with

For use with KTK-R, LP-CC and FNQ-R Class CC fuse

## Resources

### Catalogs

[CHCC1DIU~](#)

[Bussmann series complete full line catalog no. 1007](#)

### Multimedia

[Bussmann series Fuseology](#)

### Specifications and datasheets

[Eaton Specification Sheet - CHCC1DIU](#)

### Technical data sheets

[720147 10 x 38 mm Modular fuse holder](#)

---

Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

[Eaton.com/socialmedia](#)

# Eaton CHCC1DIU

Catalog Number: CHCC1DIU

Eaton Bussmann series CHCC modular fuse holder, 48 Vdc, 30A, Single-pole, With indicator



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series CHCC modular fuse holder	CHCC1DIU
	<b>UPC</b>
	051712362665
<b>Product Length/Depth</b>	<b>Product Height</b>
0.69 in	2.91 in
<b>Product Width</b>	<b>Product Weight</b>
3.28 in	0.22 lb
<b>Warranty</b>	<b>Compliances</b>
Not Applicable	RoHS Compliant
<b>Certifications</b>	
<b>Contact Manufacturer</b>	

## Electrical rating

### Amperage Rating

30 A

### Voltage rating

48 Vdc

## Physical details

### Number of Poles

Single-pole

### Operating temperature - max

90 °C

### Operating temperature - min

-20 °C

## General information

### Class

Class CC

### Used with

For use with KTK-R, LP-CC and FNQ-R Class CC fuse

## Resources

### Catalogs

[CHCC1DIU~](#)

[Bussmann series complete full line catalog no. 1007](#)

### Multimedia

[Bussmann series Fuseology](#)

### Specifications and datasheets

[Eaton Specification Sheet - CHCC1DIU](#)

### Technical data sheets

[720147 10 x 38 mm Modular fuse holder](#)

---

Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

[Eaton.com/socialmedia](#)