

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





#### CHCC1DIU 30A 600V 1P Id Class CC Fuse Block

Bussmann Fuses

Catalog Number	CHCC1DIU
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series CHCC Modular Fuse Holder, 48 VDC, 30A, Single-Pole, With Indicator
Weight per unit	
Product Category	Tools & Testers

#### **Features**

amperage rating	30 A
class	Class CC
dimensions	0.6900 IN X 3.2800 IN X 2.9100 IN
media	Yes
Voltage Rating	48 VDC
Wattage	-20

#### **Dimensions and Weight**

Size 0.689 Width X 3.275 In Depth X 2.909 In Height

### **Descriptions**

Description	30A 600V 1P ID CLASS CC FUSE BLOCK
extra long description	BUSS CHCC1DIU CCP
Features	Bussmann series Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applicat
Long Description	Eaton Bussmann series CHCC modular fuse holder, 48 Vdc, 30A, Single-pole, With indicator
Product Type	CCP
Special Features	1 Pole, For Use With KTK-R, LP-CC and FNQ-R Class CC fuse, With Indicating

#### **Manufacturer Information**

Brand	Eaton
GTIN	00051712362665
Manufacturers Part Number	CHCC1DIU
UPC	051712362665



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, an	d Categories
Category Description	FUSE BLOCKS,FUSE HOLDERS
Туре	Modular fuse holder
Packaging	
Carton	12
Weight Per each	0.125
Uses, Certifications, and Standa	ards
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Operating Temperature	-20 To 90 Dea C

Contact Manufacturer, RoHS Compliant