

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Package

Weight Per each

CHN230GF CH 5MA Gfci 2P 30A 120/240V 10kaic

Catalog Number	CHN230GF
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 30 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	0.9500 (lbs/each)
Product Category	In Circuit Breakers
atures	
dimensions	3.5000 IN X 3.5000 IN X 2.2500 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
scriptions	
Description	CH 5MA GFCI 2P 30A 120/240V 10KAIC
extra long description	ETN CHN230GF CH 5mA GFCI, 2P, 30A,
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping or mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,30 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 30A, 120/240V, 10kaic
anufacturer Information	
Brand	Eaton Corp
GTIN	00786689217242
Manufacturers Part Number	CHN230GF
UPC	786689217242
xonomies, Classifications, and (Categories
Туре	GFCI circuit breakers
ckaging	
Carton	1

10 0.95

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications,	, and Standards
-----------------------	-----------------

ocs, cei illications, and sta	iluai us
Application	Datacenters - IT Space: CI and Hyper ConvergedGeneration -
	Conventional Energy - Conventional EnergyOtherGeneration -
	Renewable Energy - Alternative EnergyMarine Vessels and
	Equipment - Marine Vessels and Equipment - Other
standard	UL 489