


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Weight Per each

## CHN235GF CH 5MA Gfci 2P 35A 120/240V 10kaic Eaton Corp

Soon	
Catalog Number	CHN235GF
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 35 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	0.8000 (lbs/each)
Product Category	In Circuit Breakers
Features	
dimensions	6.0000 IN X 3.5000 IN X 2.2500 IN
interrupt rating	10
Poles	2
Voltage Rating	120/240 V
Descriptions	
Description	CH 5MA GFCI 2P 35A 120/240V 10KAIC
extra long description	ETN CHN235GF CH 5mA GFCI, 2P, 35A,
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,35 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 35A, 120/240V, 10kaic
Manufacturer Information	Fala.
Brand	
GTIN	00786689217259
Manufacturers Part Number UPC	CHN235GF 786689217259
Taxonomies, Classifications, and C	OFOLATA TIPARATAN
Packaging Carton	1

0.8

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

ses, cei lilications, and star	iuai us
Application	Generation - Conventional Energy - Conventional EnergyMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherGeneration - Renewable Energy - Alternative
	EnergyDatacenters - IT Space: CI and Hyper ConvergedOther
standard	UL 489