


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





CHP42N225R CH Pon Loadcntr 225A Convertible 42 Space N3R *Eaton Corp*

Eaton Corp	
Catalog Number	CHP42N225R
Manufacturer	Eaton Corp
Description	Eaton CH Plug-On Neutral Loadcenter, 225A, Convertible, 42 Spaces, Nema 3R
Weight per unit	33.0 (lbs/each)
Product Category	Single Phase Convertible Load
Features	
amperage rating	225
interrupt rating	
media	Yes
number of spaces	42
Phase	1
Dimensions and Weight	
Depth	37
Height	5.19
Size	X7
Width	14.31
Descriptions	
Description	CH PON LOADCNTR 225A CONVERTIBLE 42 SPACE N3R
extra long description	ETN CHP42N225R CH PON LC, 225A, CON
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH plug-on neutral loadcenter, 225A, convertible, 42 spaces, NEMA 3R
Product Type	CH Pon LC, 225A, Conv, 42SP, N3R
Special Features	Cover included
Manufacturer Information	
Brand	Eaton
GTIN	00786689058746
Manufacturers Part Number	CHP42N225R

Brand	Eaton
GTIN	00786689058746
Manufacturers Part Number	CHP42N225R
UPC	786689058746



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	LOADCENTERS & COVERS
Туре	Convertible loadcenter
Packaging	
Carton	1
Weight Per each	33
Uses, Certifications, and Standards	
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other

UL 50,UL 67