

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Special Features

CHSPT2MICRO 120/240V 1PH 5KAIC UL1449 3RD Ed Surge Module *Eaton Corp*

| Eaton Corp | |
|------------------------|--|
| Catalog Number | CHSPT2MICR0 |
| Manufacturer | Eaton Corp |
| Description | SPD Type 2 CHSP Service Entrance Surge Protection, 120/240V Line, 150V L-N, 300V L-L McOv, 600V L-N, 1000V L-L, 800V N-G, 600V L-G VPR, 22 Ka SCCR, Nema 4 Enclosure, Single-Phase, 60 HZ, 5 Ka Nominal Current Discharge, 36 Ka Surge Current |
| Weight per unit | 1.0 (lbs/each) |
| Product Category | Surge Suprsr-Prot Dev-LN Condi |
| Features | |
| dimensions | 2.5000 IN X 3.0000 IN X 10.0000 IN |
| Phase | 1 |
| Short Circuit Rating | 22000 KA |
| Voltage Rating | 120/240 V |
| Dimensions and Weight | |
| Depth | 2.5000 |
| Height | 10.0000 |
| Width | 3.0000 |
| Descriptions | |
| Description | 120/240V 1PH 5KAIC UL1449 3RD ED SURGE MODULE |
| extra long description | ETN CHSPT2MICRO Surge-Eaton Svc Pnl |
| Features | Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t |
| Long Description | SPD Type 2 CHSP Service Entrance Surge Protection, 120/240V line, 150V L-N, 300V L-L MCOV, 600V L-N, 1000V L-L, 800V N-G, 600V L-G VPR, 22 kA SCCR, NEMA 4 enclosure, Single-phase, 60 Hz, 5 kA nominal current discharge, 36 kA surge current |
| Product Type | Surge-Eaton SVC PNL 5KA Nom, 36KA Surge |
| ÷ • | - |

CBC2007, and UBC®Zone 4

Meets or exceeds the requirments specified in IBC ®2006,



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| 1 /1 / | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | ・ヘヘキロ | IPAPI | ntari | nation |
|--------|---------------------------------------|-------|-------|-------|--------|
| | | | | | |
| | | | | | |
| | | | | | |

| Brand | Eaton | |
|---------------------------|----------------|--|
| GTIN | 00786685436869 | |
| Manufacturers Part Number | CHSPT2MICRO | |
| UPC | 786685436869 | |

Taxonomies, Classifications, and Categories

| Category Description | SURGE SUPRESSION PRODUCTS |
|----------------------|---------------------------|
| Type | Surge protection device |

Availability

| Status | Inactive |
|--------|----------|
| | |

Packaging

| Carton | 1 | |
|-----------------|---|--|
| Weight Per each | 1 | |

Uses, Certifications, and Standards

| Application | Elec Assemblies, Panels & EOEM - Electrical Assemblies and EOEMs - OtherGeneration - Renewable Energy - Generation - Renewable Energy - AftermarketDatacenters - Data Centers - AftermarketOther IT and Datacom - Other InfrastructuresOther IT and Datacom - Other IT & Datacom - AftermarketCommercial / Institutional Buildings / Structures - Commercial/Inst Bldg Strctures - AftermarketInd Facilities & Factories - Industrial Facilities/Factories - AftermarketWater and Wastewater Systems |
|-----------------------|--|
| | - Water/Wastewater Systems |
| Frequency Rating | 60 Hz |
| Operating Temperature | -40 to 50 °C |
| standard | cUL Certified,UL 1449,UL Recognized |