

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service Fax: 936-560-468

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CHT1520 Type CHT Twin BRKR 1-15/1P 1-20/1P 120/240V 10K Eaton Corp

Catalog Number	CHT1520
Manufacturer	Eaton Corp
Description	Eaton CH Thermal Magnetic Circuit Breaker, Type CHT Twin Breaker, 15-20 A, 10 Kaic, Single-Pole, 120/240V, CHT, #14-8 Aw Cu/Al, CHT, Type CH Loadcenters, 50-60 HZ, Switching Duty Rated, Hcar Rated
Weight per unit	
Product Category	1P Special Application Plug-In
itures	
dimensions	0.7000 IN X 0.5000 IN X 2.6000 IN
interrupt rating	10 kAIC
Poles	
Voltage Rating	120/240 V
scriptions	
Also Known As	Peanut
	Piggyback Breaker
	Mini-Breaker
	Half (1/2) Size Breaker
	Cheater: Breaker
	Twin Breaker
Description	
extra long description	
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position eliminating nuisance callbacks. The CHF family also includes a tr flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping or mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH thermal magnetic circuit breaker,Type CHT twin breaker,15-20 A,10 kAIC,Single-pole,120/240V,CHT,#14-8 AWG Cu/AI,CHT,Type CH Loadcenters,50-60 Hz,Switching duty rated, HCAR rated
Product Type	CHT Twin 1-15/1P 1-20/1P 120/240V 10K



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113631554
Manufacturers Part Number	CHT1520
UPC	782113631554
Taxonomies, Classifications, and Cate	egories
Category Description	Loadcenter Plug In Breakers and Accessories
Туре	Thermal magnetic circuit breakers
Packaging	
Carton	1
Weight Per each	0.28
Uses, Certifications, and Standards	
Application	Marine Vessels and Equipment - Marine Vessels and Equipment - OtherOtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL Listed, UL 489