

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CPR28 3" Rigid Coupling Threadless Crouse-Hinds

Catalog Number	CPR28
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CPR Compression Coupling, Rigid/Imc,
- -	Malleable Iron, Compression Type, 3"
Weight per unit	4.5 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
Features	
dimensions	5.2000 IN X 5.6000 IN X 5.6000 IN
Material	Malleable Iron
Descriptions	
Description	3" RIGID COUPLING THREADLESS
extra long description	MIDWEST CPR28 3 RGD CMP CPL
Features	Crouse-Hinds series rigid/IMC connectors, couplings and
	combination couplings are used to join used to join rigid/IMC
	conduit to a box or enclosure, or to couple two ends of conduit
	together. Our rigid/IMC connectors and couplings are available
	in set screw type and compression type, in both insulated and
	non-insulated versions. They are available in a variety of
	materials to suit customer preferences, including malleable iron,
	steel, zinc die cast, aluminum, stainless steel and hot dip
	galvanized mallea
Long Description	Eaton Crouse-Hinds series CPR compression coupling, Rigid/IMC,
Dreduct Turc	Malleable iron, Compression type, 3"
Product Type	3 RGD CMP CPL Concrete Tight
Special Features	Concrete right
Manufacturer Information	
Brand	Eaton
GTIN	00784564122285
Manufacturers Part Number	CPR28
UPC	784564122285
Taxonomies, Classifications, and C	Categories
Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Туре	Compression coupling
Packaging	
Carton	1
Weight Per each	4.5



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 514B, CUL