Specifications



Photo is representative

Eaton CRC3033BC

Eaton Crouse-Hinds series PowerMate CRC connector, 30A, 0.390-1.375", Three-wire, three-pole, Style 1, Copper-free aluminum, 600 Vac/250 Vdc

| General specifications | |
|-------------------------|--|
| PRODUCT NAME | Eaton Crouse-Hinds series PowerMate CRC connector |
| CATALOG NUMBER | CRC3033BC |
| UPC | 662276276376 |
| PRODUCT LENGTH/DEPTH | 6.6 in |
| PRODUCT HEIGHT | 2.56 in |
| PRODUCT WIDTH | 2.56 in |
| PRODUCT WEIGHT | 2.2 lb |



| Certifications and compliances | |
|--------------------------------|-------------------------------------|
| AREA CLASSIFICATION | Ordinary/Non-Hazardous Locations |
| STANDARDS TYPE | NEC/CEC |
| NEMA RATING | 4X |

| Product specifications | |
|------------------------|------------------------|
| AMPERAGE RATING | 30A |
| GROUNDING TYPE | Style 1 |
| CONFIGURATION | Three-wire, three-pole |
| CABLE DIAMETER | 0.390-1.375" |
| VOLTAGE RATING | 600 Vac/250 Vdc |
| MATERIAL | Copper-free aluminum |

| Resources | |
|-------------------------------|---|
| 3D CAD DRAWING PACKAGE | Eaton Crouse-Hinds CRC3033BC 3D drawing |
| BROCHURES | PowerMate Drilling Pin and Sleeve Devices brochure |
| CATALOGS | PowerMate Drilling Pin and Sleeve Devices catalog page |
| CERTIFICATION REPORTS | PowerMate Drilling Pin and Sleeve Devices cUL certification (Plugs and Connectors) PowerMate Drilling Pin and Sleeve Devices UL certification (Plugs and Connectors) |
| INSTALLATION INSTRUCTIONS | IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing |
| SPECIFICATIONS AND DATASHEETS | PowerMate Connectors Eaton Specification Sheet - CRC3033BC |

| PROJECT NAME: |
|-----------------|
| PROJECT NUMBER: |
| PREPARED BY: |
| DATE: |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com Follow us on social media to get the latest product and support information.











Specifications



Photo is representative

Eaton CRC3033BC

Eaton Crouse-Hinds series PowerMate CRC connector, 30A, 0.390-1.375", Three-wire, three-pole, Style 1, Copper-free aluminum, 600 Vac/250 Vdc

| General specifications | |
|-------------------------|--|
| PRODUCT NAME | Eaton Crouse-Hinds series PowerMate CRC connector |
| CATALOG NUMBER | CRC3033BC |
| UPC | 662276276376 |
| PRODUCT LENGTH/DEPTH | 6.6 in |
| PRODUCT HEIGHT | 2.56 in |
| PRODUCT WIDTH | 2.56 in |
| PRODUCT WEIGHT | 2.2 lb |



| Certifications and compliances | |
|--------------------------------|-------------------------------------|
| AREA CLASSIFICATION | Ordinary/Non-Hazardous Locations |
| STANDARDS TYPE | NEC/CEC |
| NEMA RATING | 4X |

| Product specifications | |
|------------------------|------------------------|
| AMPERAGE RATING | 30A |
| GROUNDING TYPE | Style 1 |
| CONFIGURATION | Three-wire, three-pole |
| CABLE DIAMETER | 0.390-1.375" |
| VOLTAGE RATING | 600 Vac/250 Vdc |
| MATERIAL | Copper-free aluminum |

| Resources | |
|-------------------------------|---|
| 3D CAD DRAWING PACKAGE | Eaton Crouse-Hinds CRC3033BC 3D drawing |
| BROCHURES | PowerMate Drilling Pin and Sleeve Devices brochure |
| CATALOGS | PowerMate Drilling Pin and Sleeve Devices catalog page |
| CERTIFICATION REPORTS | PowerMate Drilling Pin and Sleeve Devices cUL certification (Plugs and Connectors) PowerMate Drilling Pin and Sleeve Devices UL certification (Plugs and Connectors) |
| INSTALLATION INSTRUCTIONS | IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing |
| SPECIFICATIONS AND DATASHEETS | PowerMate Connectors Eaton Specification Sheet - CRC3033BC |

| PROJECT NAME: |
|-----------------|
| PROJECT NUMBER: |
| PREPARED BY: |
| DATE: |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com Follow us on social media to get the latest product and support information.









