



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CTAP202X #8-#2 Sol/STR Comp Tap Panduit Corporation

|                  |  |
|------------------|--|
| Catalog Number   | CTAP202X   |
| Manufacturer     | Panduit Corporation  |
| Description      | C-Type Copper Compression Tap, Non-Insulated, +90 °C<br>Operating Temperature, 0.80 In Overall Length, Compression<br>Terminal, 35 KV, 1 LB/Ea |
| Weight per unit  | 1.0 (lbs/each)   |
| Product Category | Large Terminals & Connectors   |

### Features

|          |                          |
|----------|--------------------------|
| Material | High Conductivity Copper |
| media    | Yes                      |

### Material, Color, and Finish

|                |        |
|----------------|--------|
| Clamp Material | Copper |
|----------------|--------|

### Dimensions and Weight

|        |     |
|--------|-----|
| Length | 0.8 |
|--------|-----|

### Descriptions

|                        |                                     |
|------------------------|-------------------------------------|
| Description            | #8-#2 SOL/STR COMP TAP              |
| extra long description | PAN CTAP2/0-2-X StructuredGround™ C |

### Manufacturer Information

|       |                |
|-------|----------------|
| Brand | PANDUIT        |
| GTIN  | 00074983821303 |
| UPC   | 074983821303   |

### Taxonomies, Classifications, and Categories

|                      |                        |
|----------------------|------------------------|
| Category Description | POWER TOOL ACCESSORIES |
| Type                 | Compression Tap        |

### Packaging

|                 |    |
|-----------------|----|
| Carton          | 1  |
| Package         | 10 |
| Weight Per each | 1  |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Utility/Ground Grid   |
| standard    | UL 467 listed for Grounding and Bonding and UL 486A for<br>electrical connections up to 35kV. |