



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



DV10250ML 10-12AWG Ylw Insldt ML Tab DSCNCT *Panduit Corporation*

| | |
|------------------|---|
| Catalog Number | DV10250ML |
| Manufacturer | Panduit Corporation |
| Description | The Vibration Resistant Male Disconnect Is Made Of Copper and Is Nickel-Plated. It Is Barrel Insulated In Yellow Vinyl Housing. It Has A Tab Size Of 0.250 X 0.032" (6.3 X 0.8 MM) and Supports A Wire Range Of 12-10 Awg (4.0-6.0 MM ²). It Is 0.98" (24.9 MM) Long and 0.25" (6.4 MM) Wide. The Disconnect Has A Funnel Entry Barrel Configuration and A Brazed Seam Barrel. It Comes In Bottles Of 50. |
| Weight per unit | 0.2100 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|----------------|--------------|
| connection | Funnel Entry |
| insulation | Vinyl |
| Material | Copper |
| Voltage Rating | 600 |
| Wire Size | 10 |

Material, Color, and Finish

| | |
|--------|---------------|
| Color | Yellow |
| Finish | Nickel Plated |

Descriptions

| | |
|------------------------|---|
| Description | 10-12AWG YLW INSLTD ML TAB DSCNCT |
| extra long description | PAN DV10-250M-L Pan-Term® DV10-250M |
| Long Description | The vibration resistant male disconnect is made of copper and is nickel-plated. It is barrel insulated in yellow vinyl housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 12-10 AWG (4.0-6.0 mm ²). It is 0.98" (24.9 mm) long and 0.25" (6.4 mm) wide. The disconnect has a funnel entry barrel configuration and a brazed seam barrel. It comes in bottles of 50. |
| Product Type | Pan-Term® DV10-250M-L Loose Piece Disconnect |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Panduit® |
| GTIN | 00074983824106 |
| Manufacturers Part Number | DV10-250M-L |
| UPC | 074983824106 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------|
| Category Description | TERMINALS |
| Type | Disconnect |

Availability

| | |
|-------------|----|
| minimum qty | 50 |
|-------------|----|

Packaging

| | |
|-----------------|------|
| Carton | 50 |
| Weight Per each | 0.21 |

Uses, Certifications, and Standards

| | |
|--------------------|---|
| Mounting | 1932-09-01 |
| Temperature Rating | 194 Degrees Fahrenheit (90 Degrees Celsius) |