



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **E10168388 2/0-4/0AWG Ylw DBL Set Screw FML Plug** *Crouse-Hinds*

Catalog Number	E10168388
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Cam-Lok J Series E1016 Plug, Up to 400A Continuous, 2/0-4/0 Awg, Yellow, Double Set Screw, Brass Contacts, Female, Thermoplastic Elastomer (Tpe), Non-Vulcanized, 600 Vac/DC
Weight per unit	0.6000 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

### **Features**

amperage rating	400
connection	Double Set Screw
dimensions	7.1800 IN X 1.5000 IN X 1.5000 IN
Poles	1
Voltage Rating	600 VAC/VDC
Wire Size	2/0 To 4/0 AWG

### **Dimensions and Weight**

Size	1.50 In Diameter X 7.18 In Length
------	-----------------------------------

### **Descriptions**

Description	2/0-4/0AWG YLW DBL SET SCREW FML PLUG
extra long description	CRS-H E1016-8388 E1016 F P NV DSS 2
Features	The Cam-Lok J series from Eaton's Crouse-Hinds Division provides the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators, indoor and outdoor lighting distribution panels, and numerous other power applications.
Long Description	Eaton Crouse-Hinds series Cam-Lok J Series E1016 plug, Up to 400A continuous, 2/0-4/0 AWG, Yellow, Double set screw, Brass contacts, Female, Thermoplastic elastomer (TPE), Non-vulcanized, 600 Vac/dc
Product Type	E1016 F P NV DSS 2/0 to 4/0 YI
Special Features	NEMA 3R Enclosure

### **Manufacturer Information**

Brand	Crouse-Hinds
GTIN	00662275131881
Manufacturers Part Number	E1016-8388
UPC	662275131881



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	PLUG

## Packaging

Carton	1
Package	10
Weight Per each	0.6

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
environmental conditions	-40 To 105 Deg C
standard	UL, CSA