



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



E22LED120GN 120V Ac/DC Green Led

Eaton Corp

Catalog Number	E22LED120GN
Manufacturer	Eaton Corp
Description	Eaton Pilot Devices - Ashville Pushbutton, 30MM, Green, Green, Green, Continuous, 120 Vac/VDC, 22.5 MM, Led Lamp, E22, 10250T, E34 and E22 Units
Weight per unit	0.1000 (lbs/each)
Product Category	Push Button Components

Dimensions and Weight

Depth	0.1
Height	0.1
Size	22.5 mm
Width	0.1

Descriptions

Description	120V AC/DC GREEN LED
extra long description	ETN E22LED120GN 120V AC/DC GREEN LE
Features	Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units.
Long Description	Eaton Pilot devices - ashville pushbutton, 30mm, Green, Green, Green, Continuous, 120 Vac/Vdc, 22.5 mm, LED lamp, E22, 10250T, E34 and E22 units
Product Type	120V Ac/DC Green Led

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113494081
Manufacturers Part Number	E22LED120GN
UPC	782113494081

Taxonomies, Classifications, and Categories

Category Description	MINATURE PILOT DEVICES.22MM
Type	Pushbutton accessory

Packaging

Carton	1
Weight Per each	0.1



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Elec Assemblies, Panels & OEM - Electrical Assemblies, Panels and OEMs
Elec Assemblies, Panels & OEM - Electrical Assemblies and OEMs - Other
Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other

standard

s Register Certified, IEC 947-5-1 MTTA, CSA Std. C22.2, BS 4794, CE Marked; UL 508, IEC 337-1, Lloyd's