

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**E30.250BK6"P Thin-Wall Heat Shrink Tubing, BK, 1/4-6"** *Minnesota Mining (3M)* 

| Catalog Number            | E30.250BK6"P  |
|---------------------------|---|
| Manufacturer              | Minnesota Mining (3M)   |
| Description               | 3M <sup>™</sup> Heat Shrink Tubing Eps-300 Is A Dual Wall Tubing Provides<br>The Advantage Of An Integral, Adhesive Lined Construction. This<br>Flame Retardant Tubing With A 3:1 Shrink Ratio Offers Insulation<br>For 600V Rated Applications. The Flexible Polyolefin Construction<br>Features An Internal Layer Of Thermoplastic Adhesive, Which<br>Offers Moisture Seal Protection In Automotive and Marine<br>Applications.   |
| Weight per unit           | 0.0080 (lbs/each)   |
| Product Category          | Splicing & Terminating Kits   |
| escriptions               |   |
| Description               | THIN-WALL HEAT SHRINK TUBING, BK, 1/4-6"  |
| extra long description    | 3M 7010350253 3M™ Thin-Wall Heat Sh   |
| Features                  | 3M <sup>™</sup> Heat Shrink Tubing EPS-300 is color coded for quick and<br>easy identification of the wire. It provides a skintight fit and<br>strain relief protection for electronic components, wire splices,<br>wire bundles and harness breakouts. This flame retardant tubing<br>has a heat shrinkable outer wall that is irradiation cross linked fo<br>abrasion resistance and helps to maintain the high flow as well as<br>good adhesion characteristics. When the tubing cools down, it<br>forms a permanent, water resistant barrier. It withstands |
| Long Description          | 3M <sup>™</sup> Heat Shrink Tubing EPS-300 is a dual wall tubing provides<br>the advantage of an integral, adhesive lined construction. This<br>flame retardant tubing with a 3:1 shrink ratio offers insulation for<br>600V rated applications. The flexible polyolefin construction<br>features an internal layer of thermoplastic adhesive, which offers<br>moisture seal protection in automotive and marine applications.  |
| Product Type              | 3M <sup>™</sup> Thin-Wall Heat Shrink Tubing Eps-300  |
| anufacturer Information   |   |
| Brand                     | 3M  |
| GTIN                      | 00051128600641  |
| Manufacturers Part Number | E30.250BK6"P  |
|                           |   |

## Taxonomies, Classifications, and Categories

UPC

| Category Description | HEAT/COLD SHRINK                   |
|----------------------|------------------------------------|
| Туре                 | Flexible Polyolefin Adhesive-Lined |

051128600641



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging                                       |       |
|---|-------|
| Carton  | 10    |
| Weight Per each                                 | 0.008 |
| Uses, Certifications, and Standards<br>standard | UL    |