

Elliott Electric Supply

2569 E. Hwy 97 78064-0000, TX Pleasanton Phone: 830-569-3390 Fax: 830-569-3608

We Deliver...Lower Cost, Quality Products, & Personal Service

1	8-		8	
1				
. 1		13		

E59M30C129A01A1 30MM Iprox Clone Ac Uns 29MM SN No Micro Eaton Corp

	FF0N #200120 # 01 # 1
Catalog Number Manufacturer	E59M30C129A01A1
	Eaton Corp
Description	Eaton Iprox Sensor, E59, Straight, 30 MM, Unshielded, 360° Viewable Led, Dual Key Micro, 200 Ma At 20-132 V, 3 Pin, <3% Sensing Range, 2-Wire Ac, No, 20-132V
Weight per unit	
Product Category	
atures	
Accuracy	< 3% sensing range
connection	
dimensions	
media	Yes
mensions and Weight	1 1011
Depth	1.1811
scriptions	
Description	30MM IPROX CLONE AC UNS 29MM SN NO MICRO
extra long description	ETN E59-M30C129A01-A1 30MM IPROX CL
Features	These unique, adaptable, field-programmable sensors utilize exclusive SmartSense technology—featuring an embedded microprocessor—to perform special sensing functions at extended ranges. These capabilities include programmable attributes, such as sensing range, output types, contact types, response time and noise immunity. No other sensor on the market offers such extensive programmability.
Long Description	Eaton iProx Sensor, E59, Straight, 30 mm, Unshielded, 360° viewable LED, Dual key micro, 200 mA at 20-132 V, 3 pin, <3% sensing range, 2-wire AC, NO, 20-132V
Product Type	30MM Iprox Clone, Ac, Uns 29MM SN, No Micro
anufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00782116183715
Manufacturers Part Number	E59-M30C129A01-A1
UPC	782116183715
xonomies, Classifications, and C	Categories
Category Description	
Туре	Programmable inductive proximity sensor



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2569 E. Hwy 97 78064-0000, TX Pleasanton Phone: 830-569-3390 Fax: 830-569-3608

Packaging	1
i ackaging	

Раскадіng Carton	1
Weight Per each	0.3
Uses, Certifications, and Standards Application	Stationary Mach Equip In Factory - Other Stationary Machinery and Equipment - In Factory
environmental conditions	NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K
standard	UL Listed, CSA Certified, CE Marked