



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## ECSR30 UI Class RK-5 Time Delay

*Bussmann Fuses*

Catalog Number	ECSR30
Manufacturer	Bussmann Fuses
Description	Eaton Edison Ecsr Fuse, Time-Delay Current-Limiting Fuse, Superior Overload and Cycling Capabilities, 30 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 10 Sec At 500%, 200 Kaic, Standard, 600 V
Weight per unit	0.1600 (lbs/each)
Product Category	Dual Element

### Features

amperage rating	30
class	Class RK5
connection	Ferrule End X Ferrule End
dimensions	11.6300 IN X 2.3400 IN X 2.3400 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC
media	Yes
Response Time	10 S at 500%
type of indicators	Non-Indicating
Voltage Rating	600 V

### Dimensions and Weight

Size	0.81 In Diameter X 5.00 In Length
------	-----------------------------------

### Descriptions

Description	UL CLASS RK-5 TIME DELAY
extra long description	EFSE ECSR30 UL CLASS RK-5 TIME DELA
Features	Edison's UL Class RK5 dual-element, time-delay fuses provide economical solutions to overcurrent protection. Available in both 250Vac and 600Vac, with 200kA RMS Sym interrupting ratings and sizes ranging from 0 to 600 amp.
Long Description	Eaton Edison ECSR fuse, Time-delay current-limiting fuse, Superior overload and cycling capabilities, 30 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 10 sec at 500%, 200 kAIC, Standard, 600 V
Product Type	UI Class RK-5 Time Delay
Special Features	Finger safe, non-indicating



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	Eaton Edison
GTIN	00782634508342
Manufacturers Part Number	ECSR30
UPC	782634508342

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

## Availability

Status	Inactive
--------	----------

## Packaging

Carton	10
Weight Per each	0.16

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked