


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Type

EDV10250Q 12-10AWG YIW ML DSCNT

Panduit Corporation

Catalog Number	EDV10250Q
Manufacturer	Panduit Corporation
Description	Stronghold EDV10-250M-Q Contractor Grade Vinyl Insulated
	Female Disconnects Are A Reliable and Economical Option That
	Withstand A Wide Range Of General-Purpose Applications. They
	Can Be Easily Inserted and Removed From The Male Disconnect
	Without The Use Of Tools. Accommodates 12-10 Awg, 250 X .03
Woight partinit	Tab Size, Are Yellow In Color, and Come In Packages Of 25.
Weight per unit	0.0500 (lbs/each) Small Terminals & Connectors
Product Category	Small reminals & connectors
eatures	
insulation	Vinyl - Barrel Insulated
Material	Brass
media	Yes
Wire Size	10
Naterial, Color, and Finish	
Color	Yellow
Finish	Tinned
Descriptions	
Description	12-10AWG YLW ML DSCNT
extra long description	PAN EDV10-250-Q StrongHold™ EDV10-2
Long Description	StrongHold EDV10-250M-Q Contractor Grade Vinyl Insulated
	Female Disconnects are a reliable and economical option that
	withstand a wide range of general-purpose applications. They
	can be easily inserted and removed from the male disconnect
	without the use of tools. Accommodates 12-10 AWG, 250 x .032
	tab size, are yellow in color, and come in packages of 25.
Product Type	Stronghold™ EDV10-250-Q Disconnect, Yellow, Vinyl 0.13"X1.03
/lanufacturer Information	
Brand	Panduit Corporation
GTIN	00074983279807
Manufacturers Part Number	EDV10-250-Q
UPC	074983279807
axonomies, Classifications, and (Categories
Category Description	TERMINALS
- · · · · · · · · · · · · · · · · · · ·	_ .

Disconnect



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

P				

Carton	25	
Package	250	
Weight Per each	0.05	
3		

Uses, Certifications, and Standards

Mounting	0.28
standard	UL Recognized, CSA, cULus, E78522, LR31212