

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ENP5151 15A-125V Plug Crouse-Hinds

Catalog Number	ENP5151
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Ark-Gard Enp Plug, 15A, 50-400 HZ, Copper-Free Aluminum, 5-15P, 125 Vac
Weight per unit	0.3800 (lbs/each)
Product Category	Pin & Sleeve Devices
eatures	
amperage rating	100
Cord Type	0.875 To 1.700 In
dimensions	3.9100 IN X 1.6000 IN X 1.6000 IN
Material	Copper-Free Aluminum
Poles	ე
Voltage Rating	600 VAC AT 50 TO 400 HZ, 250 VDC
Wire Size	4 To 1 AWG (Building), 4 To 2 AWG (Extra Flex)
Dimensions and Weight	
Length	10-1/8
Descriptions (1997)	
Description	15A-125V PLUG
extra long description	CRS-H ENP5151 15A 125V ARKGARD PLG
Features	Ark-Gard ENC connectors, ENP plugs and ENR receptacles from Eaton's Crouse-Hinds Division make it safe and easy to bring power wherever it is needed. Connectors provide versatility for making cordsets for connecting portable devices in both hazardous and non-hazardous locations. Ark-Gard plugs and receptacles are used with portable electrical equipment such a compressors, tools, lighting systems and similar devices when power requirements do not exceed 20 amperes. They are also used in areas made hazar
Long Description	Eaton Crouse-Hinds series Ark-Gard ENP plug, 15A, 50-400 Hz, Copper-free aluminum, 5-15P, 125 Vac
Product Type	15A 125V Arkgard PLG 5-20R Nema Config
Special Features	Watertight, Grounding Style 1, NEMA 4 Enclosure, Reverse

Interior



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и	•	IABLIT	· ^ ^ †	COLID	forma	STIAN
•	•	141111	41 1111	~		4

Brand	Eaton
GTIN	00782274310855
Manufacturers Part Number	ENP5151
UPC	782274310855

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	PLUG

Packaging

,,,ag.,,g		
Carton	1	
Package	2	
Weight Per each	0.38	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL 514, UL 1010, UL 1682, CSA C22.2