

EASY-TWIST™

Wire Connectors

Combination Pails

ET-CP Series



SPECIFICATIONS

- UL 486C Listed wire connector E155027.
- **Temperature Rating:** 105 °C (221 °F).
- **Voltage:** 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.

FEATURES

- Compact, easy to carry pail, also convenient for use on maintenance cart.
- 4-pack pail includes the most common Easy-twist™ connectors.



Scan QR code for mobile access to wire combinations.

CAT. NO.	FIG. NO.	PAIL CONTENTS	COLOR	WIRE RANGE	QTY. PER PAIL	STD. CTN. QTY.
ET-CP-1	1	WWC-T	Tan	22-8 AWG	70	12
		WWC-Y	Yellow	18-10 AWG	80	12
		WWC-R	Red	18-8 AWG	45	12
		WWC-B	Blue	14-6 AWG	20	12
ET-CP-2		WC-O	Orange	22-14 AWG	100	12
		WC-Y	Yellow	22-10 AWG	75	12
		WC-R	Red	22-10 AWG	50	12
		WWC-T	Tan	22-8 AWG	70	12
ET-CP-3		WC-O	Orange	22-14 AWG	100	12
		WWC-T	Tan	22-8 AWG	70	12
		WWC-Y	Yellow	18-10 AWG	80	12
ET-CP-11		WWC-R	Red	18-8 AWG	45	12
		WWC-T	Tan	22-8 AWG	40	16
		WWC-Y	Yellow	18-10 AWG	50	16
ET-CP-12		WWC-R	Red	18-8 AWG	30	16
	WWC-B	Blue	14-6 AWG	10	16	
	WC-O	Orange	22-14 AWG	65	16	
	WC-Y	Yellow	22-10 AWG	45	16	
ET-CP-13	WC-R	Red	22-10 AWG	30	16	
	WWC-T	Tan	22-8 AWG	40	16	
	WC-O	Orange	22-14 AWG	60	16	
	WWC-T	Tan	22-8 AWG	45	16	
ET-CP-14	WWC-Y	Yellow	18-10 AWG	50	16	
	WWC-R	Red	18-8 AWG	30	16	
	WC-O	Orange	22-14 AWG	65	16	
	WC-Y	Yellow	22-10 AWG	45	16	
ET-CP-15	WC-R	Red	22-10 AWG	30	16	
	WC-B	Blue	22-14 AWG	100	16	
	WC-G	Gray	22-14 AWG	120	16	
	WC-B	Blue	22-14 AWG	100	16	
	WC-O	Orange	22-14 AWG	65	16	
	WC-Y	Yellow	22-10 AWG	45	16	

EASY-TWIST™

Wire Connectors

Combination Pails

ET-CP Series



SPECIFICATIONS

- UL 486C Listed wire connector E155027.
- **Temperature Rating:** 105 °C (221 °F).
- **Voltage:** 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.

FEATURES

- Compact, easy to carry pail, also convenient for use on maintenance cart.
- 4-pack pail includes the most common Easy-twist™ connectors.



Scan QR code for mobile access to wire combinations.

CAT. NO.	FIG. NO.	PAIL CONTENTS	COLOR	WIRE RANGE	QTY. PER PAIL	STD. CTN. QTY.
ET-CP-1	1	WWC-T	Tan	22-8 AWG	70	12
		WWC-Y	Yellow	18-10 AWG	80	12
		WWC-R	Red	18-8 AWG	45	12
		WWC-B	Blue	14-6 AWG	20	12
ET-CP-2		WC-O	Orange	22-14 AWG	100	12
		WC-Y	Yellow	22-10 AWG	75	12
		WC-R	Red	22-10 AWG	50	12
		WWC-T	Tan	22-8 AWG	70	12
ET-CP-3		WC-O	Orange	22-14 AWG	100	12
		WWC-T	Tan	22-8 AWG	70	12
		WWC-Y	Yellow	18-10 AWG	80	12
ET-CP-11		WWC-R	Red	18-8 AWG	45	12
		WWC-T	Tan	22-8 AWG	40	16
		WWC-Y	Yellow	18-10 AWG	50	16
		WWC-R	Red	18-8 AWG	30	16
ET-CP-12		WWC-B	Blue	14-6 AWG	10	16
	WC-O	Orange	22-14 AWG	65	16	
	WC-Y	Yellow	22-10 AWG	45	16	
	WC-R	Red	22-10 AWG	30	16	
ET-CP-13	WWC-T	Tan	22-8 AWG	40	16	
	WC-O	Orange	22-14 AWG	60	16	
	WWC-T	Tan	22-8 AWG	45	16	
	WWC-Y	Yellow	18-10 AWG	50	16	
ET-CP-14	WWC-R	Red	18-8 AWG	30	16	
	WC-O	Orange	22-14 AWG	65	16	
	WC-Y	Yellow	22-10 AWG	45	16	
	WC-R	Red	22-10 AWG	30	16	
ET-CP-15	WC-B	Blue	22-14 AWG	100	16	
	WC-G	Gray	22-14 AWG	120	16	
	WC-B	Blue	22-14 AWG	100	16	
	WC-O	Orange	22-14 AWG	65	16	
		WC-Y	Yellow	22-10 AWG	45	16