

EYS 25% * Fill Vertical Conduit Sealing Fittings

Explosionproof, Dust-Ignitionproof, Raintight




UNILETS™ for Use with Threaded Rigid Metal Conduit and IMC.


NEC/CEC:

Class I, Division 1 and 2, Groups A, B, C, D


Class II, Division 1 and 2, Groups E, F, G

Class III

| | Trade Size (Inches) | Millimeters (Inches) | | | Kwiko™ A Cement Required Grams (Ounces) | Catalog Number | |
|---|--|----------------------|--------------|------------------|---|-----------------|-------------------|
| | | A (Length) | B (Width) | Turning Radius ① | | Malleable Iron | Almag 35 Aluminum |
|  1/2" — 3"  4" | Female | | | | | | |
| | 1/2 | 82.5 (3.25) | 28.7 (1.13) | 45.9 (1.81) | 56.7 (2.00) | EYSF-50 | EYSF-50AL |
| | 3/4 | 92.2 (3.63) | 35.0 (1.38) | 57.1 (2.25) | 85.1 (3.00) | EYSF-75 | EYSF-75AL |
| | 1 | 107.9 (4.25) | 44.5 (1.75) | 60.4 (2.38) | 141.7 (5.00) | EYSF-100 | EYSF-100AL |
| | 1-1/4 | 128.5 (5.06) | 50.8 (2.00) | 74.6 (2.94) | 311.8 (11.00) | EYSF-125 | — |
| | 1-1/2 | 139.7 (5.50) | 63.5 (2.50) | 89.9 (3.50) | 538.6 (19.00) | EYSF-150 | — |
| | 2 | 158.7 (6.25) | 74.6 (2.94) | 104.9 (4.13) | 878.8 (31.00) | EYSF-200 | — |
| | 2-1/2 | 188.9 (7.44) | 85.8 (3.38) | 120.6 (4.75) | 1304.1 (46.00) | EYSF-250 | — |
| | 3 | 215.9 (8.50) | 104.9 (4.13) | 143.0 (5.63) | 2324.7 (82.00) | EYSF-300 | — |
| | 4 | 219.2 (8.63) | 130.3 (5.13) | 165.1 (6.50) | 2608.2 (92.00) | EYSF-400 | — |
|  1/2" — 1" | Male/Female (Removable Male Nipple) | | | | | | |
| | 1/2 | 82.5 (3.25) | 28.7 (1.13) | 45.9 (1.81) | 56.7 (2.00) | EYSM-50 | EYSM-50AL |
| | 3/4 | 92.2 (3.63) | 35.5 (1.38) | 57.1 (2.25) | 85.1 (3.00) | EYSM-75 | EYSM-75AL |
| | 1 | 107.9 (4.25) | 44.5 (1.75) | 60.4 (2.38) | 141.7 (5.00) | EYSM-100 | EYSM-100AL |



EYSF
1/2" — 3"
EYSM
1/2" — 1"



EYSF
4"

* Per NEC 501.15(C)(6) seals in Class I, Division 1 and 2 must be limited to conductor fill of 25% of cross sectional area of a rigid metal conduit of the same trade size unless approved for higher percentage fill. See 40% fill sealing fittings.

① Turning radius with cover or plug removed.

◆ Indicates items in the shaded area which are UL Listed for Class I, Groups A, B, C, D; Class II, Groups E, F, G; and Class III.




EYS 25% * Fill Vertical Conduit Sealing Fittings


Explosionproof, Dust-Ignitionproof, Raintight

UNILETS™ for Use with Threaded Rigid Metal Conduit and IMC.


NEC/CEC:

Class I, Division 1 and 2, Groups A, B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

| | Trade Size (Inches) | Millimeters (Inches) | | | Kwiko™ A Cement Required Grams (Ounces) | Catalog Number | |
|---|--|----------------------|--------------|------------------|---|-----------------|-------------------|
| | | A (Length) | B (Width) | Turning Radius ① | | Malleable Iron | Almag 35 Aluminum |
|  1/2" — 3"  4" | Female | | | | | | |
| | 1/2 | 82.5 (3.25) | 28.7 (1.13) | 45.9 (1.81) | 56.7 (2.00) | EYSF-50 | EYSF-50AL |
| | 3/4 | 92.2 (3.63) | 35.0 (1.38) | 57.1 (2.25) | 85.1 (3.00) | EYSF-75 | EYSF-75AL |
| | 1 | 107.9 (4.25) | 44.5 (1.75) | 60.4 (2.38) | 141.7 (5.00) | EYSF-100 | EYSF-100AL |
| | 1-1/4 | 128.5 (5.06) | 50.8 (2.00) | 74.6 (2.94) | 311.8 (11.00) | EYSF-125 | — |
| | 1-1/2 | 139.7 (5.50) | 63.5 (2.50) | 89.9 (3.50) | 538.6 (19.00) | EYSF-150 | — |
| | 2 | 158.7 (6.25) | 74.6 (2.94) | 104.9 (4.13) | 878.8 (31.00) | EYSF-200 | — |
| | 2-1/2 | 188.9 (7.44) | 85.8 (3.38) | 120.6 (4.75) | 1304.1 (46.00) | EYSF-250 | — |
| | 3 | 215.9 (8.50) | 104.9 (4.13) | 143.0 (5.63) | 2324.7 (82.00) | EYSF-300 | — |
| | 4 | 219.2 (8.63) | 130.3 (5.13) | 165.1 (6.50) | 2608.2 (92.00) | EYSF-400 | — |
|  1/2" — 1" | Male/Female (Removable Male Nipple) | | | | | | |
| | 1/2 | 82.5 (3.25) | 28.7 (1.13) | 45.9 (1.81) | 56.7 (2.00) | EYSM-50 | EYSM-50AL |
| | 3/4 | 92.2 (3.63) | 35.5 (1.38) | 57.1 (2.25) | 85.1 (3.00) | EYSM-75 | EYSM-75AL |
| | 1 | 107.9 (4.25) | 44.5 (1.75) | 60.4 (2.38) | 141.7 (5.00) | EYSM-100 | EYSM-100AL |



EYSF
1/2" — 3"
EYSM
1/2" — 1"



EYSF
4"

* Per NEC 501.15(C)(6) seals in Class I, Division 1 and 2 must be limited to conductor fill of 25% of cross sectional area of a rigid metal conduit of the same trade size unless approved for higher percentage fill. See 40% fill sealing fittings.

① Turning radius with cover or plug removed.

◆ Indicates items in the shaded area which are UL Listed for Class I, Groups A, B, C, D; Class II, Groups E, F, G; and Class III.