

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

## EYSR4 1-1/4" Cond Seal

Crouse-Hinds	
Catalog Number	EYSR4
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eysr Retrofit Sealing Fitting, Feraloy Iron Alloy, 1-1/4"
Weight per unit	5.6 (lbs/each)
Product Category	Sealing Bodies
eatures	
dimensions	5.0000 IN X 3.0000 IN X 3.3800 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Descriptions	<u> </u>
Description	1-1/4" COND SEAL
extra long description	CRS-H EYSR4 1 1/4 RETROFIT SEALING
Features	Crouse-Hinds series EYSR retrofit sealing fittings are installed in
	rigid metal conduit systems in Class I, Division 2 hazardous
	locations to replace installed Eaton's Crouse-Hinds series EYS or
	EYD sealing fittings. EYSRs allow the replacement to be done
	without disassembly of the conduit system, and they can be
	installed in vertical or horizontal positions, indoors or outdoors.
	As with all sealing fittings, EYSRs restrict the passage of gases,
	vapors or flames from one portion of the electrical install
Long Description	Eaton Crouse-Hinds series EYSR retrofit sealing fitting, Feraloy iron alloy, 1-1/4"
Product Type	1 1/4 Retrofit Sealing FTG 5 X 3 3/8 X 3
Special Features	Horizontal/Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274793399
Manufacturers Part Number	EYSR4
UPC	782274793399
axonomies, Classifications, and (	Categories
Category Description	LIAZADDOLICI OCATIONI FITTINICO
Туре	Retrofit sealing fitting
Packaging	
0 0 0	1

5.5999

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group E F G
standard	UL 886, CSA C22.2