



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## EZ10168350K E-Z1016 M P DSS No 2 to 2/0 BK Kit *Crouse-Hinds*

Catalog Number	EZ10168350K
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Cam-Lok J Series E-Z1016 Plug, Up to 300A Continuous, #2-2/0 Awg, Black, Double Set Screw, Brass Contacts, Male, Thermoplastic Elastomer (Tpe), Single Packaged Unit, Non-Vulcanized, 600 Vac/DC
Weight per unit	1.0 (lbs/each)
Product Category	Wiring Devices

### Features

amperage rating	300
connection	Double Set Screw
dimensions	7.1400 IN X 1.4900 IN X 1.4900 IN
Voltage Rating	600 VAC/VDC
Wire Size	2 To 2/0 AWG

### Dimensions and Weight

Size	1.49 In Diameter X 7.14 In Length
------	-----------------------------------

### Descriptions

Description	E-Z1016 M P DSS NO 2 TO 2/0 BK KIT
extra long description	CRS-H E-Z1016-8350K E-Z1016 M P DSS
Features	The Cam-Lok J series from Eaton's Crouse-Hinds Division provides the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators, indoor and outdoor lighting distribution panels, and numerous other power applications.
Long Description	Eaton Crouse-Hinds series Cam-Lok J Series E-Z1016 plug, Up to 300A continuous, #2-2/0 AWG, Black, Double set screw, Brass contacts, Male, Thermoplastic elastomer (TPE), Single packaged unit, Non-vulcanized, 600 Vac/dc
Product Type	E-Z1016 M P DSS No 2 to 2/0 BK Kit
Special Features	NEMA 3R Enclosure

### Manufacturer Information

Brand	Eaton
GTIN	00662275868565
Manufacturers Part Number	E-Z1016-8350K
UPC	662275868565



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	PLUG

## Packaging

Carton	1
Weight Per each	1

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
environmental conditions	-40 To 105 Deg C
standard	UL, CSA