IN/OUT BOX[™] for Ceiling Fixtures





Adjustable Non-Metallic Box for New Construction

Easy Installation in New Construction





1 Install FA426 onto joist with a MINIMUM of four screws; (2) through front flange, (1) in each rear position. A, B, C, D above.



| Catalog Number | UPC/DEI/NAED Mfg. #018997 | Description Non-Metallic IN/OUT BOX™ | Size/ Cu Inches | Unit/Std Pkg |
|-------------------|------------------------------|---|---------------------|-----------------|
| FA426 | 40040 | Adjustable Ceiling Fixture Box | Round 20.5 cu in | 25/ctn |
| FA426G | C 40041 | Adjustable Ceiling Fixture Box w/ ground clip for Canada | Round 20.5 cu in | 25/ctn |
| | Include | s (4) installation screws, NM cab | le connector | |

Includes (4) installation screws, NM cable connector

Pre-set for 1/2" wall thickness - Depth adjustment up to 1-1/2"



2 After installing the box on joist slide plastic insert into box.

Pull NM cable through installed NM connector.





3 After installation of wall board is complete use the depth adjustment screw to adjust position of FA426 box if necessary (see Photo B). FA426 adjusts up to 1-1/2" for ceiling thickness.

Arlington's IN/OUT BOX for ceiling fixtures adjusts up to 1-1/2" to accommodate varying ceiling thicknesses, like single or double drywall.

- Pre-set for 1/2" ceiling...
 Depth adjusts up to 1-1/2"
- Always accessible depth adjustment screw allows for depth adjustment of box before or after the ceiling is in place
- Complies with 2014 NEC, 314.20 for set back boxes
- Mounts securely to joist in new construction
- Listed for fixture support up to 50 lbs
- UL/CSA Listed

Depth adjustment screw



FA426 Adjustable Fixture Box

Patent pending



1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646

www.aifittings.com

IN/OUT BOX™ Adjustable OUTLET Boxes



Adjustable Non-Metallic Outlet Boxes for New Construction





Arlington's IN/OUT OUTLET BOXES are adjustable for wall thicknesses up to 1-1/2"; perfect for use when the final thickness is not known; double drywall, change orders, tile, etc.

New! ...single-gang **horizontal** box **FA101H** for countertops and horizontal outlets...

single-gang, **low profile FA101LP**. Made for new work installations with shallower wall cavities, it's shorter than our 'regular' single-gang IN/OUT outlet box – perfect for smaller spaces.

- Complies with 2014 NEC, 314.20 for set back boxes
- · Always accessible depth adjustment screw
- Secure installation on wood or steel studs in new construction



1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717

Fax 570/562.0646 www.aifittings.com

FA426 1214/15M Patent pending











| Catalog Number | UPC/DEI/NAE Mfg. #018997 | | Number of Gangs / Cubic Inches | Unit/Std Pkg |
|-------------------|-----------------------------|------------------------------|-----------------------------------|-----------------|
| FA 101* | 04241 | Non-metallic box | Single/Vertical/21.0 cu in | 25 |
| FA101H* | 11102 | for 2x4 studs | Single/Horizontal/21.0 cu ir | 25 |
| FA102* | 04242 | w/ depth adjustment | Two-gang / 43.5 cu in | 10 |
| FA103* | 04243 | up to 1-1/2" (pre-set for | Three-gang / 65.0 cu in | 10 |
| FA104 | 04244 | 1/2" wall thickness) | Four-gang / 87.0 cu in | 10 |

with Ground Clip for use in Canada

| Catalog UPC/DEI/NA Number Mfg. #0189 | | Number of Gangs / Cubic Inches | Unit/Std Pkg |
|---|-----------------------------------|--------------------------------|-----------------|
| FA101GC* 76881 | Non-metallic box | Single/Vertical/21.0 cu in | 25 |
| FA101HGC* 11103 | w/ depth adjustment | Single/Horizontal/21.0 cu in | 25 |
| FA102GC* 76883 | up to 1-1/2" | Two-gang / 43.5 cu in | 10 |
| FA103GC* 76884 | (pre-set for 1/2" wall thickness) | Three-gang / 65.0 cu in | 10 |
| FA104GC 76885 | i/Z waii tilickiless) | Four-gang / 87.0 cu in | 10 |

| Catalog | UPC/DEI/NAED | Description OPTIONAL | Unit/Std |
|---------|--------------|---|----------|
| Number | Mfg. #018997 | | Pkg |
| FA102D | | <mark>Low Voltage Divide</mark> r FA102, FA103, FA | |



FA102D

Optional FA102D low voltage separator for use with multiple gang IN/OUT BOX



| Catalog Number | UPC/DEI/NAED Mfg. #018997 | Description IN/OUT BOX™ | Size/ Cu Inches | Unit/Std Pkg |
|-------------------|------------------------------|---|---------------------------|-----------------|
| FA101LP | 76880 | 3.25" deep, Non-metallic low profile outlet box | Single-gang 18.3 cu in | 25 |
| FA101LPG | | 3.25"deep, Non-metallic low profile outlet box, with ground clip for Canada | Single-gang 18.3 cu in | 25 |

w/ depth adjustment up to 1-1/2" (pre-set for 1/2" wall thickness)

IN/OUT BOX[™] for Ceiling Fixtures





Adjustable Non-Metallic Box for New Construction

Easy Installation in New Construction





1 Install FA426 onto joist with a MINIMUM of four screws; (2) through front flange, (1) in each rear position. A, B, C, D above.



| Catalog Number | UPC/DEI/NAED Mfg. #018997 | Description Non-Metallic IN/OUT BOX™ | Size/ Cu Inches | Unit/Std Pkg |
|-------------------|------------------------------|---|---------------------|-----------------|
| FA426 | 40040 | Adjustable Ceiling Fixture Box | Round 20.5 cu in | 25/ctn |
| FA426G | C 40041 | Adjustable Ceiling Fixture Box w/ ground clip for Canada | Round 20.5 cu in | 25/ctn |
| | Include | s (4) installation screws, NM cab | le connector | |

Includes (4) installation screws, NM cable connector

Pre-set for 1/2" wall thickness - Depth adjustment up to 1-1/2"



2 After installing the box on joist slide plastic insert into box.

Pull NM cable through installed NM connector.





3 After installation of wall board is complete use the depth adjustment screw to adjust position of FA426 box if necessary (see Photo B). FA426 adjusts up to 1-1/2" for ceiling thickness.

Arlington's IN/OUT BOX for ceiling fixtures adjusts up to 1-1/2" to accommodate varying ceiling thicknesses, like single or double drywall.

- Pre-set for 1/2" ceiling...
 Depth adjusts up to 1-1/2"
- Always accessible depth adjustment screw allows for depth adjustment of box before or after the ceiling is in place
- Complies with 2014 NEC, 314.20 for set back boxes
- Mounts securely to joist in new construction
- Listed for fixture support up to 50 lbs
- UL/CSA Listed

Depth adjustment screw



FA426 Adjustable Fixture Box

Patent pending



1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646

www.aifittings.com

IN/OUT BOX™ Adjustable OUTLET Boxes



Adjustable Non-Metallic Outlet Boxes for New Construction





Arlington's IN/OUT OUTLET BOXES are adjustable for wall thicknesses up to 1-1/2"; perfect for use when the final thickness is not known; double drywall, change orders, tile, etc.

New! ...single-gang **horizontal** box **FA101H** for countertops and horizontal outlets...

single-gang, **low profile FA101LP**. Made for new work installations with shallower wall cavities, it's shorter than our 'regular' single-gang IN/OUT outlet box – perfect for smaller spaces.

- Complies with 2014 NEC, 314.20 for set back boxes
- · Always accessible depth adjustment screw
- Secure installation on wood or steel studs in new construction



1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717

Fax 570/562.0646 www.aifittings.com

FA426 1214/15M Patent pending











| Catalog Number | UPC/DEI/NAE Mfg. #018997 | | Number of Gangs / Cubic Inches | Unit/Std Pkg |
|-------------------|-----------------------------|------------------------------|-----------------------------------|-----------------|
| FA 101* | 04241 | Non-metallic box | Single/Vertical/21.0 cu in | 25 |
| FA101H* | 11102 | for 2x4 studs | Single/Horizontal/21.0 cu ir | 25 |
| FA102* | 04242 | w/ depth adjustment | Two-gang / 43.5 cu in | 10 |
| FA103* | 04243 | up to 1-1/2" (pre-set for | Three-gang / 65.0 cu in | 10 |
| FA104 | 04244 | 1/2" wall thickness) | Four-gang / 87.0 cu in | 10 |

with Ground Clip for use in Canada

| Catalog UPC/DEI/NA Number Mfg. #0189 | | Number of Gangs / Cubic Inches | Unit/Std Pkg |
|---|-----------------------------------|--------------------------------|-----------------|
| FA101GC* 76881 | Non-metallic box | Single/Vertical/21.0 cu in | 25 |
| FA101HGC* 11103 | w/ depth adjustment | Single/Horizontal/21.0 cu in | 25 |
| FA102GC* 76883 | up to 1-1/2" | Two-gang / 43.5 cu in | 10 |
| FA103GC* 76884 | (pre-set for 1/2" wall thickness) | Three-gang / 65.0 cu in | 10 |
| FA104GC 76885 | i/Z waii tilickiless) | Four-gang / 87.0 cu in | 10 |

| Catalog | UPC/DEI/NAED | Description OPTIONAL | Unit/Std |
|---------|--------------|---|----------|
| Number | Mfg. #018997 | | Pkg |
| FA102D | | <mark>Low Voltage Divide</mark> r FA102, FA103, FA | |



FA102D

Optional FA102D low voltage separator for use with multiple gang IN/OUT BOX



| Catalog Number | UPC/DEI/NAED Mfg. #018997 | Description IN/OUT BOX™ | Size/ Cu Inches | Unit/Std Pkg |
|-------------------|------------------------------|---|---------------------------|-----------------|
| FA101LP | 76880 | 3.25" deep, Non-metallic low profile outlet box | Single-gang 18.3 cu in | 25 |
| FA101LPG | | 3.25"deep, Non-metallic low profile outlet box, with ground clip for Canada | Single-gang 18.3 cu in | 25 |

w/ depth adjustment up to 1-1/2" (pre-set for 1/2" wall thickness)