

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FDC3 1G Dev Box Crouse-Hinds

Catalog Number	FDC3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feraloy Iron Alloy, Single-Gang, C Shape, 1"
Weight per unit	3.7 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(1) Each End
dimensions	6.2800 IN X 2.6900 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Allov

Dimensions and Weight

Size	1 in
------	------

Desc

Description	1G DEV BOX
extra long description	CRS-H FDC3 1 THRUFEED CST IRON FD B
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feraloy iron alloy, Single-gang, C shape, 1"
Product Type	1 Thrufeed CST Iron FD BX SGL GNG MT Lug
Special Features	Configuration Type FDC, Dimension 2-3/4 In Width X 2-11/16 In Depth X 6-9/32 In Height

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274398303
Manufacturers Part Number	FDC3
UPC	782274398303

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

P				

Carton	1	
Package	2	
Weight Per each	3.68	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH
standard	UL 514, CSA C22.2, Federal Specification W-C-5860