

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## FNQR4 4A 600V TD Class CC Fuse

Bussmann Fuses

Catalog Number	FNQR4
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CC Fuse, FNQ, Time-Delay,
	Dual-Element Current Limiting Fuse, 4 A, Rejection Style Fuse,
	Interrupting Rating Of 200KA At 600vac
Weight per unit	0.0200 (lbs/each)
Product Category	Small Dimension Fuses

### **Features**

amperage rating	4
connection	Ferrule End X Ferrule End
dimensions	1.5000 IN X 0.4100 IN X 0.4100 IN
Fuse Class	Class CC
interrupt rating	200 kAIC
Material	Melamine Tube
media	Yes
Response Time	12 S at 200%
Voltage Rating	600 V

### **Dimensions and Weight**

		•	
5	Size	13/32 In Diameter X 1-1/2 In Length	

### **Descriptions**

Description	4A 600V TD CLASS CC FUSE
extra long description	BUSS FNQ-R-4 CLASS CC TIME DELAY
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Long Description	Eaton Bussmann Series Class CC fuse, FNQ, time-delay, dual-element current limiting fuse, 4 A, rejection style fuse, interrupting rating of 200kA at 600Vac
Product Type	Class CC Time Delay
Special Features	Rejection Style



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	•		
$N/I \cap MI$	ıfacturer	Intorm	NATIAN
11/1/41/11	HACHHEL		14111111
IVIGIIC	mactar cr		14 (1011

Brand	Eaton
GTIN	00051712147095
Manufacturers Part Number	FNO-R-4
UPC	051712147095

### **Taxonomies, Classifications, and Categories**

Category Description	MIDGET FUSES
Type	FUSE

### **Packaging**

Carton	10
Weight Per each	0.02

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant