

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### FP30111648 Thin-Wall Heat Shrink Tubing, 1/16 - 48", BK Minnesota Mining (3M)

| Catalog Number            | FP30111648  |
|---------------------------|---|
| Manufacturer              | Minnesota Mining (3M)   |
| Description               | 3M <sup>™</sup> Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall<br>Tubing That Provides A Balance Of Electrical, Physical and<br>Chemical Properties, Making It Ideal For Industrial and Military<br>Applications. This Tubing Has A 2:1 Shrink Ratio and Provides<br>Flame Retardant Insulation For 600V Rated Applications. It Has A<br>Flexible Polyolefin Construction That Offers Moisture Seal<br>Protection.   |
| Weight per unit           | 0.0272 (lbs/each)   |
| Product Category          | Splicing & Terminating Kits   |
| criptions                 |   |
| Description               | THIN-WALL HEAT SHRINK TUBING, 1/16 - 48", BK  |
| extra long description    | 3M 7000133629 3M™ Heat Shrink Thin-   |
| Features                  | 3M <sup>™</sup> Heat Shrink Tubing FP-301 is color coded for quick and eas<br>identification of the wire. This split resistant, flame retardant<br>tubing is used as shrink fit, electrical insulation over cable splices<br>or terminations. The high expansion ratio tubing is mechanically<br>tough, easily markable and resists cold flow. It is ideal for<br>lightweight wire harness covering, fire resistant covering, wire<br>marking, wire bundling and component packaging. It withstands<br>temperatures of 67 to 275 degrees F (55 to 135 degrees |
| Long Description          | 3M <sup>™</sup> Heat Shrink Tubing FP-301 is a general purpose, thin wall<br>tubing that provides a balance of electrical, physical and chemica<br>properties, making it ideal for industrial and military applications<br>This tubing has a 2:1 shrink ratio and provides flame retardant<br>insulation for 600V rated applications. It has a flexible polyolefin<br>construction that offers moisture seal protection.  |
| Product Type              | 3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301   |
| nufacturer Information    |   |
| Brand                     | 3M  |
| GTIN                      | 00051128599655  |
| Manufacturers Part Number | FP0.063BK48"S   |
| UPC                       | 051128599655  |

### Taxonomies, Classifications, and Categories

| Category Description | HEAT/COLD SHRINK              |
|----------------------|-------------------------------|
| Туре                 | Thin-Wall Flexible Polyolefin |



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### Packaging

| Carton          |        |
|-----------------|--------|
| Package         | 25     |
| Weight Per each | 0.0272 |

#### Uses, Certifications, and Standards

standard

UL Recognized, CSA Certified, ABS, and AMS 3636 & 3637