

## **E**LLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

FP30131648CLEAR Heat Shrink Th	in-Wall Tubing 3/16-48"-Clear-25PC
$\Lambda$ (in a constant $\Lambda$ (in the set (2) $\Lambda$ )	5

Minnesota Mining (3M)	
Catalog Number	FP30131648CLEAR
Manufacturer	Minnesota Mining (3M)
Description	3M <sup>™</sup> Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection.
Weight per unit	0.0334 (lbs/each)
Product Category	Splicing & Terminating Kits
scriptions	
Description	HEAT SHRINK THIN-WALL TUBING 3/16-48"-CLEAR-25PC
extra long description	3M 7000133490 3M <sup>™</sup> Heat Shrink Thin-
Features	3M <sup>™</sup> Heat Shrink Tubing FP-301 is color coded for quick and easy
Long Description	identification of the wire. This split resistant, flame retardant tubing is used as shrink fit, electrical insulation over cable splices or terminations. The high expansion ratio tubing is mechanically tough, easily markable and resists cold flow. It is ideal for lightweight wire harness covering, fire resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of 67 to 275 degrees F (55 to 135 degrees 3M <sup>™</sup> Heat Shrink Tubing FP-301 is a general purpose, thin wall
	tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
Product Type	3M <sup>™</sup> Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301
Special Features	Flexible, Polyolefin
nufacturer Information	
Brand	
GTIN	00051128595718
Manufacturers Part Number	FP0.188CR48"S
UPC	051128595718
conomies, Classifications, and C	-
Category Description	
Туре	Single (Thin) Wall



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	25
Weight Per each	0.0334
Uses, Certifications, and Standards standard	UL, CSA, ABS