



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FP30134X200CLEAR Heat Shrink Thin-Wall Tubing FP-301-3/4-Clear-200' *Minnesota Mining (3M)*

| | |
|------------------|---|
| Catalog Number | FP30134X200CLEAR |
| Manufacturer | Minnesota Mining (3M) |
| Description | 3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection. |
| Weight per unit | 0.0238 (lbs/each) |
| Product Category | Insulating Materials |

Features

| | |
|---------------------------------|----------------------------|
| continuous operating temperatur | -67 degrees to 275 degrees |
| Dielectric Strength | 900 |
| flammability | Pass |
| Inside Diameter | 0.375 |
| outside diameter | 0.75 |
| Shrink Ratio | 2:1 |

Material, Color, and Finish

| | |
|-------|-----------|
| Color | Colorless |
|-------|-----------|

Dimensions and Weight

| | |
|-----------|------|
| Length | 2400 |
| Thickness | 0.03 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Descriptions

| | |
|------------------------|---|
| Description | HEAT SHRINK THIN-WALL TUBING FP-301-3/4-CLEAR-200' |
| extra long description | 3M FP0.750CR200'L FP 3/4 CR SPL |
| Features | 3M™ Heat Shrink Tubing FP-301 is color-coded for quick and easy identification of the wire. This split-resistant tubing is used as shrink-fit, electrical insulation over cable splices or terminations. The high-expansion-ratio tubing is mechanically tough, easily markable and resists cold flow. It is perfect for lightweight wire-harness covering, fire-resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of -67 to 275 degrees F (-55 to 135 degrees C). SAE-AMS-DT |
| Long Description | 3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection. |
| Product Type | FP 3/4 CR SPL 5300750CR |
| Special Features | Flexible, Polyolefin |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | 3M |
| GTIN | 00054007085317 |
| Manufacturers Part Number | FP0.750CR200'L |
| UPC | 054007085317 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------|
| Category Description | HEAT/COLD SHRINK |
| Type | Single (Thin) Wall |

Availability

| | |
|-------------|-----|
| minimum qty | 200 |
|-------------|-----|

Packaging

| | |
|-----------------|--------|
| Carton | 200 |
| Weight Per each | 0.0238 |

Uses, Certifications, and Standards

| | |
|----------|--------------|
| standard | UL, CSA, ABS |
|----------|--------------|