

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR2 2A 250V Dual-Element Time-Delay Class RK5 Fuse Bussmann Fuses

Catalog Number	FRNR2
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay,
	Dual-Element, Current Limiting Fuse, 2 A, Non-Indicating Fuse,
	Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 125 VDC
Weight per unit	
Product Category	Dual Element
eatures	
amperage rating	2
connection	Ferrule End X Ferrule End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC
imensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
escriptions	
Description	2A 250V DUAL-ELEMENT TIME-DELAY CLASS RK5 FUSE
extra long description	
Features	Bussmann's UL Class RK5 Fusetron product offering provides
	energy efficient advanced protection with its dual-element,
	time-delay construction and is available with optional open fuse
	indication on select ratings. Available in both 250Vac and
	600Vac, 200kA RMS Sym interrupting rating and sizes ranging
	from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of
	time-delay at 500 of rated current (8 seconds for 1/10-30A sizes
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay,
	dual-element, current limiting fuse, 2 A, non-indicating fuse,
Draduat Tura	interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc
Product Type	Fusetron Dual-Element Class RK5
Nanufacturer Information	
Brand	Eaton Bussmann series
GTIN	00051712507141
Manufacturers Part Number	FRN-R-2
UPC	051712507141



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.04
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked