


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Product Type

**Special Features** 

#### FRNR3 3A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Soon Bussilialiii ruses	EDAIDO
Catalog Number	FRNR3
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRN-R Fuse, 3 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 8 Sec At 500%, 200 Kaic At 250 V, 20 Kaic At 125 VDC, Standard, 250 V, 125 VDC
Weight per unit	0.0500 (lbs/each)
Product Category	
Features	
amperage rating	3 A
class	Class DVE
connection	Ferrule End X Ferrule End
dimensions	
element	Dual
interrupt rating	200 kAIC at 250 Vac20 kAIC at 125 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
Descriptions	
Description	3A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-3 FUSETRON DUAL-ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann series FRN-R fuse, 3 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 8 sec at 500%, 200 kAIC at 250 V, 20 kAIC at 125 Vdc, Standard, 250 V, 125 Vdc

Fusetron Dual-Element Class RK5

Finger safe, power loss 3.48 w



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Eaton
GTIN	00051712506991
Manufacturers Part Number	FRN-R-3
UPC	051712506991

#### **Taxonomies, Classifications, and Categories**

Category Description	Fuses & Fuse Accessories
Type	FUSF

#### **Packaging**

Carton	10
Weight Per each	0.05

### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked