

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR3210 3-2/10A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

-	
Catalog Number	FRNR3210
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay, Dual-Element, Current Limiting Fuse, 3.2 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 125 VDC
Weight per unit	
Product Category	
eatures	
amperage rating	3.2
connection	Ferrule End X Ferrule End
dimensions	3.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	
interrupt rating	
media	Vec
Response Time	
Voltage Rating	
Dimensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
Descriptions	
Description	3-2/10A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-3-2/10 FUSETRON DUAL-ELE
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) o time-delay at 500 of rated current (8 seconds for 1/10-30A sizes
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 3.2 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 125 Vdc
Product Type	Fusetron Dual-Element Class RK5
Special Features	Finger Safe



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712507189
Manufacturers Part Number	FRN-R-3-2/10
UPC	051712507189
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.03
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked