

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Special Features

FRSR214 2-1/4A 600V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Dussilialiii ruses	
Catalog Number	FRSR214
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRS-R, Time-Delay, Dual-Element, Current Limiting Fuse, 2.25 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Weight per unit	0.1500 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	2.25
connection	Ferrule End X Ferrule End
dimensions	5.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
media	
Response Time	
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 5.00 In Length
Descriptions	
Description	2-1/4A 600V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRS-R-2-1/4 FUSETRON DUAL ELEM
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 2.25 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
-	

Renewable



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	COOPER BUSSMANN
GTIN	00051712508155
Manufacturers Part Number	FRS-R-2-1/4
UPC	051712508155

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Tyne	FUSF

Packaging

onaging		
Carton	10	
Weight Per each	0.15	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked