

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Product Type

**Special Features** 

## FRSR350 Fusetron Dual Element Fuse Class RK5

Catalog Number	FRSR350
Manufacturer	Purcemonn Fusco
Description	Eaton Bussmann Series Class RK5 Fuse, FRS-R, Time-Delay, Dual-Element, Current Limiting Fuse, 350 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Weight per unit	2.3 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	350
connection	Blade End X Blade End
dimensions	
element	
Fuse Class	Class RK5
interrupt rating	20 kAIC at 300 Vdc200 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	2.34 In Diameter X 11.63 In Length
Descriptions	
Description	FUSETRON DUAL ELEMENT FUSE CLASS RK5
extra long description	BUSS FRS-R-350 FUSETRON DUAL ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes)
Long Description	Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 350 A, non-indicating fuse,

interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

Fusetron Dual Element Fuse Class RK5

Renewable



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Eaton Bussmann series
GTIN	00051712508520
Manufacturers Part Number	FRS-R-350
UPC	051712508520

#### **Taxonomies, Classifications, and Categories**

Category Description	Fuses & Fuse Accessories
Type	FUSF

#### **Packaging**

onaging	
Carton	1
Weight Per each	2.34

### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked